TITLE 327 WATER POLLUTION CONTROL DIVISION

Final Rule LSA Document #14-58

DIGEST

Amends 327 IAC 2-1-6 and 327 IAC 2-1.5-8 concerning revisions to Indiana's aquatic life and human health surface water quality criteria (WQC) for select metals to reflect updates based on current science and National Recommended Water Quality Criteria (NRWQC) at Section 304(a) of the Clean Water Act (CWA). Effective 30 days after filing with the Publisher.

HISTORY

First Notice of Comment Period: March 5, 2014, Indiana Register (DIN: <u>20140305-IR-327140058FNA</u>). Second Notice of Comment Period: November 15, 2017, Indiana Register (DIN:

20171115-IR-327140058SNA).

Notice of Public Hearing: November 15, 2017, Indiana Register (DIN: <u>20171115-IR-327140058PHA</u>). Continuation of Second Notice of Comment Period: December 20, 2017, Indiana Register (DIN:

20171220-IR-327140058SCA).

Change in Notice of Public Hearing: January 8, 2020, Indiana Register (DIN: <u>20200108-IR-327140058CHA</u>). Change in Notice of Public Hearing: January 22, 2020, Indiana Register (DIN:

20200122-IR-327140058CHA).

Change in Notice of Public Hearing: April 8, 2020, Indiana Register (DIN: 20200408-IR-327140058CHA).

Change in Notice of Public Hearing: September 23, 2020, Indiana Register (DIN:

20200923-IR-327140058CHA).

Date of First Hearing: November 18, 2020.

Proposed Rule: April 21, 2021, Indiana Register (DIN: 20210421-IR-327140058PRA).

Notice of Second Hearing: April 21, 2021, Indiana Register (DIN: 20210421-IR-327140058PHA).

Third Comment Period: April 21, 2021, Indiana Register (DIN: 20210421-IR-327140058PRA).

Change in Notice of Public Hearing: June 30, 2021, Indiana Register (DIN: 20210630-IR-327140058CHA).

Date of Second Hearing: August 11, 2021.

327 IAC 2-1-6; 327 IAC 2-1.5-8

SECTION 1. 327 IAC 2-1-6 IS AMENDED TO READ AS FOLLOWS:

327 IAC 2-1-6 Minimum surface water quality criteria

Authority: IC 13-14-8-2; IC 13-14-8-3; IC 13-18-4-3

Affected: IC 13-11-2-258; IC 13-18-4; IC 13-30-2-1; IC 14-22-9

Sec. 6. (a) The following are minimum surface water quality conditions:

- (1) All surface waters, at all times and at all places, including waters within the **a** mixing zone, shall meet the minimum conditions of being **must be** free from substances, materials, floating debris, oil, or scum attributable to municipal, industrial, agricultural, and other land use practices, or other discharges that do any of the following:
 - (A) Will Settle to form putrescent or otherwise objectionable deposits.
 - (B) Are Occur in amounts sufficient to be unsightly or deleterious.
 - (C) Produce:
 - (i) color;
 - (ii) visible oil sheen;
 - (iii) odor; or
 - (iv) other conditions;

in such degree as to create an extent that creates a nuisance.

- (D) Are **Occur** in concentrations or combinations that will cause or contribute to the growth of aquatic plants or algae to such **a** degree as to:
- (i) create a nuisance;
- (ii) be unsightly; or
- (iii) otherwise impair the designated uses of the surface waters.
- (E) Are **Occur** in amounts sufficient to be acutely toxic to, or to otherwise severely injure or kill, aquatic life, other animals, plants, or humans. To assure ensure protection of aquatic life, concentrations of toxic

Date: Jan 27,2022 3:06:53PM EST DIN: 20211201-IR-327140058FRA Page 1

substances shall **must** not exceed the final acute value (FAV = 2 (AAC)) in the undiluted discharge or the acute aquatic criterion (AAC) outside the zone of initial dilution or, if applicable, the zone of discharge-induced mixing. **The following apply where applicable:**

- (i) For certain substances, an AAC is established and set forth specified in:
- (AA) subdivision (3), Table 6-1, which incorporates subdivision (3), Table 6-2; which table incorporates subdivision (4), Table 6-3; and
- (BB) subdivision (5). (6).
- (ii) for substances for which an AAC is not specified in subdivision (3), Table 6-1, subdivision (3), Table 6-2, or subdivision (5), An AAC can may be calculated by the commissioner using the procedures in section 8.2 of this rule and for substances for which an AAC is not specified in:
- (AA) subdivision (3), Table 6-1, which incorporates subdivision (5), Table 6-2; or (BB) subdivision (6).
- (iii) The AAC determined under item (i) or (ii) may be modified on a site-specific basis to reflect local conditions in accordance with section 8.9 of this rule. This
- **(F)** Clause shall **(E)** does not apply to the chemical control of plants and animals when that control is performed in compliance with approval conditions specified by the Indiana department of natural resources as provided by IC 14-22-9.
- (2) At All times, all surface waters outside of mixing zones shall must be free of substances in concentrations that, on the basis of available scientific data, are believed to be sufficient to injure, be chronically toxic to, or be carcinogenic, mutagenic, or teratogenic to humans, animals, aquatic life, or plants. To assure protection against the adverse effects identified in this subdivision, The following requirements to ensure protection against the adverse effects identified in this subdivision are established: as follows:
 - (A) A toxic substance or pollutant shall must not be present in such surface waters outside of mixing zones in concentrations that exceed the most stringent of the following continuous criterion concentrations (CCCs):
 - (i) A chronic aquatic criterion (CAC) to protect aquatic life from chronic toxic effects.
 - (ii) A terrestrial life cycle safe concentration (TLSC) to protect terrestrial organisms from toxic effects that may result from the consumption of aquatic organisms or water from the waterbody.
 - (iii) A human life cycle safe concentration (HLSC) to protect human health from toxic effects that may result from the consumption of aquatic organisms or drinking water from the waterbody.
 - (iv) For carcinogenic substances, a criterion to protect human health from unacceptable cancer risk of greater than one (1) additional occurrence of cancer per one hundred thousand (100,000) population.
 - (B) For certain substances, one (1) or more of the CCCs identified in clause (A) are established and set forth specified in:
 - (i) subdivision (3), Table 6-1, which incorporates subdivision (5), Table 6-2;
 - (ii) subdivision (3), Table 6-2 (which table incorporates subdivision (4), (4)(A), Table 6-3), and subdivision (5). 6-1a;
 - (iii) subdivision (4)(B), Table 6-1b;
 - (iv) subdivision (6); and
 - (v) subdivision (7), Table 6-4.
 - (C) For substances for which one (1) or more of the CCCs identified in clause (A) are not specified in subdivision (3), Table 6-1, subdivision (3), Table 6-2, or subdivision (5), such Criterion or criteria may be calculated by the commissioner using the corresponding procedures prescribed by sections 8.3 through 8.6 of this rule for substances for which a CCC identified in clause (A) is not specified in:
 - (i) subdivision (3), Table 6-1, which incorporates subdivision (5), Table 6-2;
 - (ii) subdivision (4)(A), Table 6-1a;
 - (iii) subdivision (4)(B), Table 6-1b;
 - (iv) subdivision (6); or
 - (v) subdivision (7), Table 6-4.
 - (D) A CCC determined under clause (B) (B)(i), (B)(iv), (B)(v), or (C) may be modified on a site-specific basis to reflect local conditions in accordance with section 8.9 of this rule.
 - (E) The CAC and TLSC for a substance apply in all surface waters outside **of** a mixing zone for a discharge of that substance. Similarly,
 - **(F)** In **surface** waters where a public water system intake is not present or is unaffected by the discharge of a substance, the HLSC and the carcinogenic criterion for that substance based on consumption of organisms from the waterbody and only incidental ingestion of water shall apply to all surface waters outside **of** the mixing zone for a discharge of that substance.
 - **(G)** In surface waters where a public water system intake is present, the HLSC and the carcinogenic criterion for a substance based on consumption of organisms and potable water from the waterbody shall apply at the point of the public water system intake.
- (3) The following establishes Surface water quality criteria for the protection of aquatic life for specific

substances are as follows:

Table 6-1
Surface Water Quality Criteria for Specific Substances

AAC (Maximum)		CCC					
, a to (maxima	••••			Point of Water			
			Mixing Zone	Intake			
		Aquatic Life (CAC) (4-Day	Human Health (30-Day	Human Health			
Substances	÷	Average)	Average)	(30-Day Average)			
Metals (µg/l)				· · · · · · · · · · · · · · · · · · ·			
(Total recoverable)	-						
Antimony			45,000 (T)	146 (T)			
Arsenic (III)	#	#	0.175 (C)	0.022 (C)			
Barium				1,000 (D)			
Beryllium			1.17 (C)	0.068 (C)			
Cadmium	#	#		10 (D)			
Chromium (III)	#	#	3,433,000 (T)	170,000 (T)			
Chromium (VI)	#	#		50 (D)			
Copper	#	#					
Lead	#	#		50 (D)			
Mercury\$	2.4	0.012	0.15 (T)	0.14 (T)			
Nickel	#	#	100 (T)	13.4 (T)			
Selenium	130*	35 ##		10 (D)			
Silver	#			50 (D)			
Thallium			48 (T)	13 (T)			
Zinc	#	#					
Organics (µg/I)	_						
Acrolein			780 (T)	320 (T)			
Acrylonitrile			6.5 (C)	0.58 (C)			
Aldrin\$	1.5*		0.00079 (C)	0.00074 (C)			
Benzene			400 (C)	6.6 (C)			
Benzidine			0.0053 (C)	0.0012 (C)			
Carbon Tetrachloride			69.4 (C)	4.0 (C)			
Chlordane\$	1.2*	0.0043	0.0048 (C)	0.0046 (C)			
Chlorinated Benzenes							
Monochlorobenzene				488 (T)			
1,2,4,5-Tetrachlorobenzene\$			48 (T)	38 (T)			
Pentachlorobenzene\$			85 (T)	74 (T)			
Hexachlorbenzene\$			0.0074 (C)	0.0072 (C)			
Chlorinated Ethanes							
1,2-dichloroethane			2,430 (C)	9.4 (C)			
1,1,1-trichloroethane			1,030,000 (T)	18,400 (T)			
1,1,2-trichloroethane			418 (C)	6.0 (C)			
1,1,2,2-tetrachloroethane			107 (C)	1.7 (C)			
Hexachloroethane			87.4 (C)	19 (C)			
Chlorinated Phenols				(-)			
2,4,5-trichlorophenol				2,600 (T)			
2,4,6-trichlorophenol			36 (C)	12 (C)			
Chloroalkyl Ethers			4 000 (T)	0.4.7.(T)			
bis(2-chloroisopropyl) ether			4,360 (T)	34.7 (T)			
bis(chloromethyl) ether			0.018 (C)	0.000038 (C)			
bis(2-chloroethyl) ether			13.6 (C)	0.3 (C)			
Chloroform	0.000	0.044	157 (C)	1.9 (C)			
Chlorpyrifos	0.083	0.041	0.00004 (6)	0.00004 (2)			
DDT\$	0.55*	0.0010	0.00024 (C)	0.00024 (C)			
Dichlorobenzenes			2,600 (T)	400 (T)			

Indiana Register					
Dichlorobenzidine			0.2 (C)	0.1 (C)	
1,1-dichloroethylene			18.5 (C)	0.33 (C)	
2,4-dichlorophenol				3,090 (T)	
Dichloropropenes			14,100 (T)	87 (T)	
Dieldrin\$	1.3*	0.0019	0.00076 (C)	0.00071 (C)	
2,4-dinitrotoluene			91 (C)	1.1 (C)	
Dioxin (2,3,7,8-TCDD)\$			0.0000001 (C)	0.0000001 (C)	
1,2-diphenylhydrazine	0.44*	0.050	5.6 (C)	0.422 (C)	
Endosulfan	0.11*	0.056	159 (T)	74 (T)	
Endrin\$	0.09*	0.0023	2 200 (T)	1.0 (D)	
Ethylbenzene			3,280 (T)	1,400 (T)	
Fluoranthene			54 (T)	42 (T)	
Halomethanes Heptachlor\$	0.26*	0.0038	157 (C)	1.9 (C) 0.0028 (C)	
Hexachlorobutadiene\$	U.20	0.0030	0.0028 (C) 500 (C)	0.0028 (C) 4.47 (C)	
Hexachlorocyclohexane			300 (0)	4.47 (0)	
(HCH)					
alpha HCH\$			0.31 (C)	0.09 (C)	
beta HCH\$			0.55 (C)	0.16 (C)	
gamma HCH (Lindane)\$	1.0*	0.080	0.63 (C)	0.19 (C)	
Technical HCH\$			0.41 (C)	0.12 (C)	
Hexachlorocyclopentadiene				206 (T)	
Isophorone			520,000 (T)	5,200 (T)	
Nitrobenzene				19,800 (T)	
Nitrophenols			705 (T)	40.4 (T)	
4,6-dinitro-o-cresol			765 (T)	13.4 (T)	
Dinitrophenol			14,300 (T)	70 (T)	
Nitrosamines			40.4.(0)	0.000 (0)	
N-nitrosodiethylamine			12.4 (C)	0.008 (C)	
N-nitrosodimethylamine N-nitrosodibutylamine			160 (C)	0.014 (C)	
N-nitrosodiphenylamine			5.9 (C) 161 (C)	0.064 (C) 49 (C)	
N-nitrosopyrrolidine			919 (C)	49 (C) 0.16 (C)	
Parathion	0.065	0.013	313 (0)	0.10 (0)	
Pentachlorophenol	e ^(1.005 [pH]-4.830)	e ^(1.005 [pH]-5.290)		1,000 (T)	
•	e	e ·			
Phenol				3,500 (T)	
Phthalate Esters			0.000.000 (T)	242 000 (T)	
Dimethyl phthalate			2,900,000 (T)	313,000 (T)	
Diethyl phthalate			1,800,000 (T)	350,000 (T)	
Dibutyl phthalate Di-2-ethylhexyl phthalate			154,000 (T) 50,000 (T)	34,000 (T) 15,000 (T)	
Polychlorinated Biphenyls		0.014	0.00079 (C)	15,000 (1) 0.00079 (C)	
(PCBs)\$		0.014	,	,	
Carcinogenic Polynuclear Aromatic Hydrocarbons (PAHs)			0.31 (C)	0.028 (C)	
Tetrachloroethylene			88.5 (C)	8 (C)	
Toluene			424,000 (T)	14,300 (T)	
Toxaphene\$	0.73	0.0002	0.0073 (C)	0.0071 (C)	
Trichloroethylene			807 (C)	27 (C)	
Vinyl Chloride			5,246 (C)	20 (C)	
Other Substances				. ,	
Asbestos (fibers/liter)	_			300,000 (C)	
Chloride (mg/l)	**	**			
Chlorine					
(Total Residual) (μg/l)	19	11			

Chlorine ^a (mg/l)			
(intermittent, total residual)		0.2	
Cyanide (Free) (µg/l)	22	5.2	
Cyanide (Total) (µg/l)			200 (D)
Nitrate-N + Nitrite-N (mg/l)			10 (D)
Nitrite-N (mg/l)			1.0 (D)

Fluoride shall not exceed two (2.0) mg/l in all surface waters outside of the mixing zone except the Ohio River and Interstate Wabash River where it shall not exceed one (1.0) mg/l outside of the mixing zone. Sulfate shall not exceed the criteria established in subdivision (6) in all surface waters outside of the mixing zone.

#The AAC and CAC for this substance are established in Table 6-2.

*One-half (1/2) of the final acute value (FAV) as calculated by procedures developed by U.S. EPA in 1980. This value would correspond to acute aquatic values calculated using IDEM procedures or U.S. EPA procedures developed in 1985 in which the calculated FAV is divided by two (2) to reduce acute toxicity. **The AAC and CAC for this substance are established in subdivision (5).

T-derived from threshold toxicity.

C derived from nonthreshold cancer risk.

D derived from drinking water standards, equal to or less than threshold toxicity.

\$This substance is a bioaccumulative chemical of concern.

^aTo be considered an intermittent discharge, total residual chlorine shall not be detected in the discharge for a period of more than forty (40) minutes in duration, and such periods shall be separated by at least five (5) hours.

Table 6-2
Surface Water Quality Criteria for Specific Substances

Substances	AAC Conve s AAC (Maximum) (µg/l) Factors		CAC (4-Day Average) (µg/l)	CAC Conversion Factors
Metals				
(dissolved)^[1]				
Arsenic (III)	WER ^[2] (360)	1.000	WER ^[2] (190)	1.000
Cadmium	WER ^[2] (e ^{(1.128}	1.136672-[(In	$WER^{[2]}(e^{(0.7852})$	1.101672-[(In hardness)
	[In(hardness)] 3.828))	hardness) (0.041838)]	[In(hardness)]-3.490))	(0.041838)]
Chromium	WER ^[2] (e ^{(0.819}	0.316	WER ^[2] (e ^{(0.8190}	0.860
(III)	[In(hardness)]+3.688)		[In(hardness)]+1.561))	
Chromium (VI)	WER ^[2] (16)	0.982	WER ^[2] (11)	0.962
Copper	WER ^[2] (e ^{(0.9422}	0.960	WER ^[2] (e ^{(0.8545}	0.960
	[In(hardness)]-1.464)		(ln(hardness)]-1.465)	
Lead	WER ^[2] (e ^{(1.273}	1.46203-[(ln	WER ^[2] (e ^{(1.273}	1.46203-[(In hardness)
	[In(hardness)]-1.460))	hardness)	[In(hardness)]-4.705)}	(0.145712)]
	F01	(0.145712)]	TO1 (0.0.400	
Nickel	WER ^[2] (e ^{(0.8460}	0.998	WER ^[2] (e ^{(0.8460}	0.997
	[In(hardness)]+3.3612)}		[In(hardness)]+1.1645)	
Silver	WER ^[2] (e ^{(1.72}	0.85		
	[In(hardness)]-6.52)/2[3]			
Zine	WER ^[2] (e ^{(0.8473}	0.978	$WER^{[2]}(e^{(0.8473})$	0.986
	[In(hardness)]+0.8604))		[In(hardness)]+0.7614)	

^[1] The AAC and CAC columns of this table contain total recoverable metals criteria (numeric and hardness-based). The criterion for the dissolved metal is calculated by multiplying the appropriate conversion factor by the AAC or CAC. This dissolved AAC or CAC shall be rounded to two (2) significant digits, except when the criteria are used as intermediate values in a calculation, such as in the calculation of water quality-based

Page 5

Date: Jan 27,2022 3:06:53PM EST DIN: 20211201-IR-327140058FRA

effluent limitations (WQBELs).
[23] A value of one (1) shall be used for the water-effect ratio (WER) unless an alternate value is established under

section 8.9 of this rule.

[3] One half (1/2) of the FAV as calculated by procedures developed by U.S. EPA in 1980. This value would correspond to acute aquatic values calculated using IDEM procedures or U.S. EPA procedures developed in 1985 in which the calculated FAV is divided by two (2) to reduce acute toxicity.

Table 6-1 Surface Water Quality Criteria for the Protection of Aquatic Life

CAS Number	Substances	Acute Aquatic Criteria (AAC) (Maximum) (μg/l)	AAC Conversion Factors (CF)	Chronic Aquatic Criteria (CAC) (4-Day Average) (µg/l)	CAC Conversion Factors (CF)
	Metals				
7440382	Arsenic ^[1]	WER(340)(CF)	1.000	WER(150)(CF)	1.000
7440439	Cadmium ^{[1][2]}	WER (e ^(0.9789[InH] - 3.866))	1.136672-	WER (e ^(0.7977[InH]-3.909))	1.101672-
		(CF)	[lnH]0.041838	(CF)	[InH]0.041838
16065831	Chromium (III) ^{[1][2]}	WER (e ^(0.819[inH]+3.7256))(CF)	0.316	WER (e ^(0.819[InH]+0.6848))(CF)	0.860
18540299	Chromium (VI) ^[1]	WER(16)(CF)	0.982	WER(11)(CF)	0.962
7440508	Copper ^{[1][2]}	WER (e ^(0.9422[InH]-1.464))(CF)	0.960	WER (e ^(0.8545[InH]-1.465)) (CF)	0.960
7439921	Lead ^{[1][2]}	WER	1.46203-	WER (e ^(1.273[InH]-4.705))	1.46203-
		(e ^(1.273[InH]-1.460))(CF)	[lnH]0.145712	(CF)	[InH]0.145712
7439976	Mercury ^{[3][4]}	2.4	NA	0.012	NA
7440020	Nickel ^{[1][2]}	WER (e ^(0.846[InH]+2.255))(CF)	0.998	WER (e ^(0.846[InH]+0.0584))(CF)	0.997
7440224	Silver ^{[1][2][5]}	WER (e ^(1.72[InH]-6.59) /2)(CF)	0.85		
7440666	Zinc ^{[1][2]}	WER (e ^{(0.8473[InH]} +0.884))(CF)	0.978	WER (e ^(0.8473[InH]+0.884)) (CF)	0.986
	Organics				
309002	Aldrin ^{[4][5]}	1.5	NA		NA
57749	Chlordane ^{[4][5]}	1.2	NA	0.0043	NA
2921882	Chlorpyrifos	0.083	NA	0.041	NA
50293	DDT ^{[4][5]}	0.55	NA	0.0010	NA
60571	Dieldrin ^{[4][5]}	1.3	NA	0.0019	NA
	Endosulfan ^[5]	0.11	NA	0.056	NA
72208	Endrin ^{[4][5]}	0.09	NA	0.0023	NA
76448	Heptachlor ^{[4][5]}	0.26	NA	0.0038	NA
58899	Gamma HCH (Lindane) ^{[4][5]}	1.0	NA	0.080	NA
56382	Parathion	0.065	NA	0.013	NA
87865	Pentachlorophenol	e ^(1.005[pH]-4.830)	NA	e ^(1.005[pH]-5.290)	NA
	Polychlorinated Biphenyls (PCBs) ^[4]		NA	0.014	NA
8001352	Toxaphene ^[4]	0.73	NA	0.0002	NA
	Other Substances	<u> </u>			
7782505	Chlorine (Total Residual)	19	NA	11	NA
7782505	Chlorine (intermittent, total residual) ^[6]			200	NA

57125	Cyanide (free)	22	NA	5.2	NA				
Selenium CAC are specified in subdivision (4).									
Chloride AAC	and CAC are specified in	subdivision (6).							

[1] Aquatic life criteria for these metals are expressed as a dissolved concentration and are calculated using the water-effect ratio (WER) and the specified conversion factor (CF). The AAC and CAC for a dissolved metal are calculated by multiplying the WER by the criterion value or formula, and then by the appropriate CF. A value of one (1) must be used for the WER unless an alternate value is established under section 8.9 of this rule. The dissolved AAC and CAC must be rounded to two (2) significant digits, except when the criteria are used as intermediate values in a calculation, such as in the calculation of water quality-based effluent limitations (WQBELs).

[2] The hardness values used in the equations for these criteria must not be greater than 400 mg/l as calcium carbonate (CaCO₃), and the criteria at a hardness of 400 mg/l as CaCO₃ are used for a water hardness above 400 mg/l as CaCO₃. The term "InH" is the natural log of hardness.

[3] Aquatic life criteria for this metal are expressed as a total recoverable concentration.

These substances are bioaccumulative chemicals of concern.

[5] The AAC for these substances is one-half (1/2) of the Final Acute Value (FAV) as calculated by procedures developed by U.S. EPA in 1980. This value would correspond to acute aquatic values calculated using procedures of the department or U.S. EPA procedures developed in 1985 in which the calculated FAV is divided by two (2) to reduce acute toxicity.

^[6]To be considered an intermittent discharge, total residual chlorine must not be detected in the discharge for a period of more than forty (40) minutes in duration, and these time periods must be separated by at least five (5) hours.

- (4) Surface water quality criterion for selenium must meet the following:
 - (A) The surface water quality criterion for selenium, except for waters where the department has made, and U.S. EPA has approved, a site-specific determination that the criterion in Table 6-1b are applicable, is as follows:

Table 6-1a Surface Water Quality Aquatic Life Criterion for Selenium (CAS # 7782492)

	Chronic Aquatic Criterion (CAC)									
Media Type	Fish [*]	Tissue ^[1]	Water Column ^{[5][7]}							
Criterion Element	Egg/Ovary ^[2]	Fish Whole-Body or Muscle ^[3]	Monthly Average Exposure	Intermittent Exposure ^[6]						
Magnitude	15.1 mg/kg dw	8.5 mg/kg dw whole-body or 11.3 mg/kg dw muscle (skinless, boneless filet)	1.5 µg/l in lentic aquatic systems 3.1 µg/l in lotic aquatic systems	$WQC_{\text{int}} =$ $\frac{WQC_{30\text{-day}} - C_{\text{bkgrnd}}(1\text{-}f_{\text{int}})}{f_{\text{int}}}$						
Duration	Instantaneous measurement ^[4]	Instantaneous measurement ^[4]	Thirty (30) days	Number of days per month with an elevated concentration						
Frequency	Not to be exceeded	Not to be exceeded	Not more than once in three (3) years on average	Not more than once in three (3) years on average						

 $^{[1]}$ Fish tissue elements are expressed as steady-state; the aquatic system should not be experiencing new or increasing inputs of selenium.

^[2]Egg or ovary supersedes any whole-body, muscle, or water column element when fish egg or ovary concentrations are measured. Any proposal to sample egg or ovary fish tissue must be submitted to the department for review and approval prior to initiation of sampling, and the department will evaluate all representative egg or ovary fish tissue data to determine compliance with this criterion element. [3] Fish whole-body or muscle tissue supersedes the water column element when both fish tissue and water concentrations are measured. Any proposal to sample fish whole-body or muscle tissue must be submitted to the department for review and approval prior to initiation of sampling, and the department will evaluate all representative fish whole-body or muscle tissue data to determine compliance with this criterion element.

[4] Fish tissue data provide instantaneous point measurements that reflect integrative accumulation of

selenium over time and space in fish populations at a given site.

[5] Water column values are the applicable criterion element in the absence of steady-state condition fish tissue data and for fishless waters. Water column values are based on dissolved total selenium in water and are derived from fish tissue values via bioaccumulation modeling. Instead of the requirements in 327 IAC 5-2-11.1(b)(2), the allowable mixing zone dilution will be determined by applying the guideline in 327 IAC 2-1-4 to the thirty (30) day, ten (10) year (Q_{30,10}) low flow of the receiving stream for the chronic aquatic criterion (CAC) water column criterion element applicable to lotic aquatic systems, in the absence of site-specific mixing zone data.

[6] Intermittent Exposure Equation variables mean the following:

WQC is the water column intermittent element.

 $WQC_{30\text{-day}}^{\text{int}}$ is the water column monthly element for either lentic or lotic waters. $C_{\text{bkgrnd}}^{\text{bkgrnd}}$ is the average background selenium concentration. $f_{\text{int}}^{\text{bkgrnd}}$ is the fraction of any 30-day period during which elevated selenium concentrations occur, with f_{int} assigned a value \geq 0.033 (corresponding to one (1) day).

^[7]The water column criterion element may be modified on a site-specific basis in accordance with clause

(B) The surface water quality criterion for selenium, where the department has made, and U.S. EPA has approved, a site-specific determination that fishes in the Order Acipenseriformes (Order includes sturgeon and paddlefish) do not occur at the site, is as follows:

Table 6-1b Site-specific Surface Water Quality Aquatic Life Criterion for Selenium (CAS # 7782492) in Non-Acipenseriformes (No Sturgeon or Paddlefish) Waters^[1]

	Chro	nic Aquatic Criterion ((CAC)			
Media Type	Fish T	issue ^[2]	Water Column ^{[6][8]}			
Criterion Element	Egg/Ovary ^[3]	Fish Whole-Body or Muscle ^[4]	Monthly Average Exposure	Intermittent Exposure ^[7]		
Magnitude	19.0 mg/kg dw	9.5 mg/kg dw whole-body or 13.1 mg/kg dw muscle (skinless, boneless filet)	2.7 μg/l in lentic aquatic systems 5.5 μg/l in lotic aquatic systems	$WQC_{\text{int}} = \frac{WQC_{30\text{-day}} - C_{\text{bkgrnd}}(1\text{-}f_{\text{int}})}{f_{\text{int}}}$		
Duration	Instantaneous measurement ^[5]	Instantaneous measurement ^[5]	Thirty (30) days	Number of days per month with an elevated concentration		
Frequency	Not to be exceeded	Not to be exceeded	Not more than once in three (3) years on average	Not more than once in three (3) years on average		

 $^{^{[1]}}$ This criterion is applicable to surface waters for which the department has made, and U.S. EPA has approved, a site-specific determination that fishes in the Order Acipenseriformes do not occur at the site. In making this determination, the department must comply with the procedures in clause (D).

^[2]Fish tissue elements are expressed as steady-state; the aquatic system should not be experiencing new or increasing inputs of selenium.

^[3] Eqq or ovary supersedes any whole-body, muscle, or water column element when fish egg or ovary concentrations are measured. Any proposal to sample egg or ovary fish tissue must be submitted to the department for review and approval prior to initiation of sampling, and the department will evaluate all representative egg or ovary fish tissue data to determine compliance with this criterion element.

^[4]Fish whole-body or muscle tissue supersedes the water column element when both fish tissue and water concentrations are measured. Any proposal to sample fish whole-body or muscle tissue must be submitted to the department for review and approval prior to initiation of sampling, and the department will evaluate all representative fish whole-body or muscle tissue data to determine compliance with this

 $^{^{[5]}}$ Fish tissue data provide instantaneous point measurements that reflect integrative accumulation of selenium over time and space in fish populations at a given site.

^[6]Water column values are the applicable criterion element in the absence of steady-state condition fish

tissue data and for fishless waters. Water column values are based on dissolved total selenium in water and are derived from fish tissue values via bioaccumulation modeling. Instead of the requirements in 327 IAC 5-2-11.1(b)(2), the allowable mixing zone dilution will be determined by applying the guideline in 327 IAC 2-1-4 to the thirty (30) day, ten (10) year (Q_{30.10}) low flow of the receiving stream for the chronic aquatic criterion (CAC) water column criterion element applicable to lotic aquatic systems, in the absence of site-specific mixing zone data.

^[7]Intermittent Exposure Equation variables mean the following:

WQC is the water column intermittent element.

 $WQC_{30-\text{day}}^{\text{int}}$ is the water column monthly element for either lentic or lotic waters. C_{bkgrad} is the average background selenium concentration.

 $C_{\text{bkgrnd}}^{30\text{-}day}$ the average background selenium concentration. $f_{\text{int}}^{\text{bkgrnd}}$ is the fraction of any 30-day period during which elevated selenium concentrations occur, with f_{int} assigned a value \geq 0.033 (corresponding to one (1) day).

[8] The water column criterion element may be modified on a site-specific basis in accordance with clause (C).

- (C) Modification of the selenium water column criterion element must be achieved according to the following:
- (i) Site-specific water column criterion elements must be derived using either the empirical bioaccumulation factor (BAF) or mechanistic modeling method provided in Aquatic Life Ambient Water Quality Criterion for Selenium – Freshwater, EPA-822-R-16-006, Appendix K: Translation of a Selenium Fish Tissue Criterion Element to a Site-Specific Water Column Value (June 2016)*.
- (ii) Any proposal to derive a site-specific water column criterion element must be submitted to the department for review and approval of the methodology and sampling plan prior to initiation of sampling. The department shall evaluate and approve the applicability of and use of all representative data used to derive a site-specific water column criterion element.
- (iii) Any proposal to derive a site-specific water column criterion element must be protective of downstream designated uses for aquatic life and human health.
- (iv) Upon receipt of an application for a site-specific water column criterion element, the department shall do the following:
- (AA) Publish on the department website all pertinent information about the proposed site-specific modification.
- (BB) Provide notice and request comment on the application.
- (v) Upon approval of a site-specific water column criterion element, the department shall do the following:
- (AA) Publish a notice in the Indiana Register.
- (BB) Place on the department's website all pertinent information about the approved site-specific modification.
- (CC) Submit the site-specific modification to U.S. EPA for approval.
- (DD) If approved by U.S. EPA, incorporate the site-specific modification into the water quality standards during the next revision of the water quality standards.
- (vi) Site-specific modifications of this criterion must not be incorporated into a final NPDES permit or used for other Clean Water Act purposes until approved by U.S. EPA.
- (D) Upon receipt of an application for a site-specific determination that fishes in the Order Acipenseriformes (Order includes sturgeon and paddlefish) do not occur at the site, the department shall do the following:
- (i) Review available species occurrence and distribution information and do one (1) of the following:
- (AA) Make a tentative determination that fishes in the Order Acipenseriformes do not occur at the
- (BB) Make a determination that fishes in the Order Acipenseriformes occur at the site and deny the application.
- (ii) Upon a tentative determination that fishes in the Order Acipenseriformes do not occur at the site, the department shall do the following:
- (AA) Publish on the department's website all pertinent information about the proposed site-specific determination.
- (BB) Provide notice and request comment on the tentative decision.
- (iii) Upon a final determination that fishes in the Order Acipenseriformes do not occur at the site, the department shall do the following:
- (AA) Publish a notice in the Indiana Register.
- (BB) Place on the department's website all pertinent information about the approved site-specific

DIN: 20211201-IR-327140058FRA

(CC) Submit the site-specific modification to U.S. EPA for approval.

(DD) If approved by U.S. EPA, incorporate the site-specific modification into the water quality standards during the next revision of the water quality standards.

(iv) Site-specific modifications of this criterion must not be incorporated into a final NPDES permit or used for other Clean Water Act purposes until approved by U.S. EPA.

(4) (5) The following establishes dissolved AAC and CAC for certain metals at selected hardness values calculated from the equations and conversion factors in subdivision (3), Table 6-2 and using 6-1, with a value of one (1) used for the WER are as follows:

Table 6-3 6-2 Metals Concentrations in Micrograms Per Liter; Hardness in Milligrams Per Liter CaCO₂

	Arsen	Arsenic (III)		Cadmium		Chromium (III)		um (VI)	Cop	per
Hardness	AAC	CAC	AAC	CAC	AAC	CAC	AAC	CAC	AAC	CAC
50	360 340	190 150	1.7 0.94	0.62 0.43	310 320	100 42	16	11	8.9	6.3
100	360 340	190 150	3.7 1.8	1.0 0.72	550 570	180 74	16	11	17	11
150	360 340	190 150	5.7 2.6	1.4 0.97	760 790	250 100	16	11	25	16
200	360 340	190 150	7.8 3.4	1.7 1.2	970 1, 000	310 130	16	11	33	21
250	360 340	190 150	10 4.2	2.0 1.4	1200	380 160	16	11	40	25
300	360 340	190 150	12 5.0	2.3 1.6	1300 1,400	440 180	16	11	48	29
350	360 340	190 150	14 5.8	2.6 1.8	1500 1, 600	500 210	16	11	55	33
400	360 340	190 150	17 6.5	2.9 2.0	1700 1,800	550 230	16	11	63	37
450	360	190	19	3.1	1900	610	16	11	70	41
500	360	190	21	3.4	2100	670	16	11	78	45

	Lead		Nic	Nickel		Silver		Zinc	
Hardness	AAC	CAC	AAC	CAC	AAC	CAC	AAC	CAC	
50	30	1.2	790 260	87 29	0.52 0.49	-	64 65	58 66	
100	65	2.5	1400 470	160 52	1.7 1.6	_	110 120	100 120	
150	100	3.9	2000 660	220 73	3.5 3.2	-	160 170	150 170	
200	140	5.3	2500 840	280 93	5.7 5.3	-	210	190 210	
250	170	6.7	3100 1,000	340 110	8.3 7.8	-	250	230 260	
300	210	8.1	3600 1, 200	400 130	11	-	290 300	270 300	
350	240	9.5	4100 1,400	450 150	15 14	-	330 340	300 340	
400	280	11	4600 1,500	510 170	19 17	-	370 380	340 380	
450	320	12	5100	560	23	_	410	370	
500	350	14	5500	610	27	_	450	410	

^[1] The dissolved metals criteria in this table have been rounded to two (2) significant digits in accordance with subdivision (3), Table 6-2. **Table 6-1.** The equations and conversion factors in subdivision (3), Table 6-2 shall Table 6-1 must be used instead of the criteria in this table when disselved metals these criteria are used as intermediate values in a calculation, such as in the calculation of WQBELs.

Where: C = chloride AAC (maximum) in mg/l.

⁽⁵⁾ The following establishes (6) Surface water quality criteria for chloride for protection of aquatic life are as follows:

⁽A) The following provides the AAC for chloride as a function of hardness (in mg/l as CaCO₃) and sulfate (in mg/l) in surface waters is calculated using the following formula: $C = 287.8 \text{ (hardness)}^{0.205797} \text{ (sulfate)}^{-0.07452}$

⁽B) The following provides the CAC for chloride as a function of hardness (in mg/l as CaCO₃) and sulfate (in

Culfoto

mg/l) in surface waters **is calculated using the following formula:** $C = 177.87 \text{ (hardness)}^{0.205797} \text{ (sulfate)}^{-0.07452}$

Where: C = chloride CAC (4-day average) in mg/l.

- (C) The following This clause applies to the AAC and CAC for chloride provided in this subdivision, as follows:
- (i) Chloride criteria may only be established based on a sulfate concentration greater than the water quality criterion for sulfate, as established under subdivision (6), (8), where the water quality criterion for sulfate has been modified on a site-specific basis in accordance with either the:
- (AA) variance provisions under section 8.8 of this rule; or the
- (BB) site-specific criteria provisions under section 8.9 of this rule.
- (ii) The AAC and CAC for chloride calculated from the equations in this subdivision shall must be rounded to the nearest whole numbers, except when the criteria are used as intermediate values in a calculation, such as in the calculation of WQBELs.
- (D) The following establishes the AAC for chloride in mg/l at selected concentrations of hardness (in mg/l as CaCO₃) and sulfate with the understanding that the equation in clause (A) shall be used instead of the criteria in this clause when chloride criteria are used as intermediate values in a calculation, such as in the calculation of WQBELs: is as follows:

Table 6-3a^[1] Hardness (mg/l)

Sulfate											
(mg/l)	50	100	150	200	250	300	350	400	450	500	
15	526	607	660	700	733	761	785	807	827	845	
20	515	594	646	685	717	745	769	790	809	827	
25	506	584	635	674	705	732	756	777	796	813	
50	481	555	603	640	670	695	718	738	756	773	
100	457	527	573	608	636	660	682	701	718	734	
150	443	511	556	589	617	641	661	680	697	712	
200	434	500	544	577	604	627	647	665	682	697	
250	427	492	535	567	594	617	637	654	671	685	
300	421	485	528	560	586	609	628	646	661	676	
350	416	480	522	553	579	602	621	638	654	668	
400	412	475	516	548	574	596	615	632	647	662	
450	408	471	512	543	569	590	609	626	642	656	
500	405	467	508	539	564	586	605	622	637	651	

^[1] The equation in clause (A) must be used instead of the criteria in this table when chloride criteria are used as intermediate values in a calculation, such as in the calculation of WQBELs.

Table 6-3b^[1] Hardness (mg/l)

Sullate										
(mg/l)	50	100	150	200	250	300	350	400	450	500
15	325	375	408	433	453	470	485	499	511	522
20	318	367	399	423	443	460	475	488	500	511
25	313	361	392	416	436	453	467	480	492	503
50	297	343	373	395	414	430	444	456	467	477
100	282	326	354	375	393	408	421	433	444	453
150	274	316	343	364	381	396	409	420	430	440
200	268	309	336	357	373	388	400	411	421	431
250	264	304	331	351	367	381	394	404	414	423
300	260	300	326	346	362	376	388	399	409	418
350	257	297	322	342	358	372	384	394	404	413
400	255	294	319	339	355	368	380	391	400	409
450	252	291	316	336	351	365	377	387	397	405

Date: Jan 27,2022 3:06:53PM EST DIN: 20211201-IR-327140058FRA

⁽E) The following establishes the CAC for chloride in mg/l at selected concentrations of hardness (in mg/l as CaCO2) and sulfate with the understanding that the equation in clause (B) shall be used instead of the criteria in this clause when chloride criteria are used as intermediate values in a calculation, such as in the calculation of WQBELs: is as follows:

500 250 289 314 333 349 362 374 384 394 402

(7) Surface water quality criteria for protection of human health for specific substances are as follows:

		Table 6-4		
		Surface Water Quality Criteria for Protection	n of Human Health ^[1]	
			Continuous Criterio	on Concentrations
CAS Number		Substances	Outside of Mixing Zone (µg/I)	Point of Water Intake (µg/l)
	M	etals (total recoverable)		
7440360		Antimony	640 (T)	5.6 (T)
		Arsenic III	0.175 (C)	0.022 (C)
7440393		Barium		1,000 (D)
7440508		Copper		1,300 (D)
7439976		Mercury ^[2]	0.15 (T)	0.14 (T)
7440020		Nickel	4,600 (T)	610 (T)
7782492		Selenium	4,200 (T)	170 (T)
7440280		Thallium	48 (T)	13 (T)
7440666		Zinc	26,000 (T)	7,400 (T)
40000	0	rganics	T === (== \tau -	
107028		Acrolein	780 (T)	320 (T)
107131		Acrylonitrile	6.5 (C)	0.58 (C)
309002		Aldrin ^[2]	0.00079 (C)	0.00074 (C)
71432		Benzene	400 (C)	6.6 (C)
92875		Benzidine	0.0053 (C)	0.0012 (C)
56235		Carbon Tetrachloride	69.4 (C)	4.0 (C)
57749		Chlordane ^[2]	0.0048 (C)	0.0046 (C)
	CI	lorinated Benzenes	•	
108907		Monochlorobenzene		488 (T)
95943		1,2,4,5-Tetrachlorobenzene ^[2]	48 (T)	38 (T)
608935		Pentachlorobenzene ^[2]	85 (T)	74 (T)
118741		Hexachlorobenzene ^[2]	0.0074 (C)	0.0072 (C)
	CI	nlorinated Ethanes		
107062		1,2-dichloroethane	2,430 (C)	9.4 (C)
71556		1,1,1-trichloroethane	1,030,000 (T)	18,400 (T)
79005		1,1,2-trichloroethane	418 (C)	6.0 (C)
79345		1,1,2,2-tetrachloroethane	107 (C)	1.7 (C)
67721	_	Hexachloroethane	87.4 (C)	19 (C)
05054	C	nlorinated Phenols		0 000 (T)
95954		2,4,5-trichlorophenol 2,4,6-trichlorophenol	26 (0)	2,600 (T)
88062		2,4,6-tricniorophenoi hioroalkyl Ethers	36 (C)	12 (C)
		bis(2-chloroisopropyl) ether	4,360 (T)	34.7 (T)
542881		bis(chloromethyl) ether	0.018 (C)	0.000038 (C)
111444		bis(2-chloroethyl) ether	13.6 (C)	0.3 (C)
67663		Chloroform	157 (C)	1.9 (C)
50293	1	DDT ^[2]	0.00024 (C)	0.00024 (C)
		Dichlorobenzenes	2,600 (T)	400 (T)
		Dichlorobenzidine	0.2 (C)	0.1 (C)

^[1] The equation in clause (B) must be used instead of the criteria in this table when chloride criteria are used as intermediate values in a calculation, such as in the calculation of WQBELs.

75354	1,1-dichloroethylene	18.5 (C)	0.33 (C)
120832	2,4-dichlorophenol	10.5 (0)	3,090 (T)
.20002	Dichloropropenes	14,100 (T)	87 (T)
60571	Dieldrin ^[2]	0.00076 (C)	0.00071 (C)
121142	2,4-dinitrotoluene	` ′	1.1 (C)
		91 (C)	
1746016	Dioxin (2,3,7,8-TCDD) ^[2]	0.0000001 (C)	0.0000001 (C)
122667	1,2-diphenylhydrazine	5.6 (C)	0.422 (C)
	Endosulfan	159 (T)	74 (T)
72208	Endrin ^[2]		1.0 (D)
100414	Ethylbenzene	3,280 (T)	1,400 (T)
206440	Fluoranthene	54 (T)	42 (T)
	Halomethanes	157 (C)	1.9 (C)
76448	Heptachlor ^[2]	0.0028 (C)	0.0028 (C)
87683	Hexachlorobutadiene ^[2]	500 (C)	4.47 (C)
	Hexachlorocyclohexane (HCH)		
319846	alpha HCH ^[2]	0.31 (C)	0.09 (C)
319857	beta HCH ^[2]	0.55 (C)	0.16 (C)
58899	gamma HCH (Lindane) ^[2]	0.63 (C)	0.19 (C)
608731	Technical HCH ^[2]	0.41 (C)	0.12 (C)
77474	Hexachlorocyclopentadiene		206 (T)
78591	Isophorone	520,000 (T)	5,200 (T)
98953	Nitrobenzene		19,800 (T)
	Nitrophenols		
534521	4,6-dinitro-o-cresol	765 (T)	13.4 (T)
25550587	Dinitrophenol	14,300 (T)	70 (T)
	Nitrosamines		T
55185	N-nitrosodiethylamine	12.4 (C)	0.008 (C)
62759	N-nitrosodimethylamine	160 (C)	0.014 (C)
924163	N-nitrosodibutylamine	5.9 (C)	0.064 (C)
86306 930552	N-nitrosodiphenylamine	161 (C)	49 (C)
930552 87865	N-nitrosopyrrolidine Pentachlorophenol	919 (C)	0.16 (C) 1,000 (T)
108952	Phenol		3,500 (T)
100932	Phthalate Esters		3,300 (1)
131113	Dimethyl phthalate	2,900,000 (T)	313,000 (T)
84662	Diethyl phthalate	1,800,000 (T)	350,000 (T)
84742	Dibutyl phthalate	154,000 (T)	34,000 (T)
117817	Di-2-ethylhexyl phthalate	50,000 (T)	15,000 (T)
	Polychlorinated Biphenyls (PCBs) ^[2]	0.00079 (C)	0.00079 (C)
	Carcinogenic Polynuclear Aromatic Hydrocarbons (PAHs)	0.31 (C)	0.028 (C)
127184	Tetrachloroethylene	88.5 (C)	8 (C)
108883	Toluene	424,000 (T)	14,300 (T)
8001352	Toxaphene ^[2]	0.0073 (C)	0.0071 (C)
79016	Trichloroethylene	807 (C)	27 (C)
75014	Vinyl Chloride	5,246 (C)	20 (C)
	Other Substances	-,= ·• (•)	(-)
1332214	Asbestos (fibers/liter)		300,000 (C)
		I	• • • • • • • • • • • • • • • • • • • •

57125 Cyanide (Total)	200 (D)						
^[1] The human health criteria are thirty (30) day average criteria.							
T-derived from threshold toxicity							
C-derived from nonthreshold cancer risk							
D-derived from drinking water standards, equal to or less than threshold toxicity							
[2]This substance is a bioaccumulative chemical of concern.							

- (6) The following establishes (8) Surface water quality criteria for sulfate that shall must not be exceeded in all surface waters outside of the a mixing zone are as follows:
 - (A) The following provides surface water quality criteria for sulfate in mg/l for the specified ranges of hardness (in mg/l as CaCO₂) or chloride (in mg/l), or both, are as follows:
 - (i) If the hardness concentration of surface waters is greater than or equal to one hundred (100) mg/l but less than or equal to five hundred (500) mg/l, and if the chloride concentration of surface waters is greater than or equal to five (5) mg/l but less than twenty-five (25) mg/l, then:

 $C = [-57.478 + 5.79 \text{ (hardness)} + 54.163 \text{ (chloride)}] \times 0.65$

Where: C = sulfate criterion in mg/l.

(ii) If the hardness concentration of surface waters is greater than or equal to one hundred (100) mg/l but less than or equal to five hundred (500) mg/l, and if the chloride concentration of surface waters is greater than or equal to twenty-five (25) mg/l but less than or equal to five hundred (500) mg/l, then:

 $C = [1276.7 + 5.508 \text{ (hardness)} - 1.457 \text{ (chloride)}] \times 0.65$

Where: C = sulfate criterion in mg/l.

- (iii) If the hardness concentration of surface waters is less than one hundred (100) mg/l and the chloride concentration of surface waters is less than or equal to five hundred (500) mg/l, the sulfate criterion is five hundred (500) mg/l.
- (iv) If the hardness concentration of surface waters is greater than five hundred (500) mg/l and the chloride concentration of surface waters is greater than or equal to five (5) mg/l, but less than or equal to five hundred (500) mg/l, the sulfate criterion shall be is calculated using a hardness concentration of five hundred (500) mg/l and the equation in item (i) or (ii) that applies to the chloride concentration.
- (v) If the chloride concentration of surface waters is less than five (5) mg/l, the sulfate criterion is five hundred (500) mg/l.
- (B) The following This clause applies to the surface water quality criteria for sulfate provided in clause (A), as follows:
- (i) Sulfate criteria may only be established based on a chloride concentration greater than the CAC for chloride established under subdivision (5) (6) where the CAC for chloride has been modified on a site-specific basis in accordance with either the:
- (AA) variance provisions under section 8.8 of this rule; or the
- (BB) site-specific criteria provisions under section 8.9 of this rule.
- (ii) The surface water quality criteria for sulfate calculated from equations in clause (A) shall **must** be rounded to the nearest whole numbers, except when the criteria are used as intermediate values in a calculation, such as in the calculation of WQBELs.
- (C) The following establishes surface water quality criteria for sulfate in mg/l at selected concentrations of hardness (in mg/l as CaCO₃) and chloride with the understanding that the equations in clause (A) shall be used instead of the criteria in this clause when sulfate criteria are used as intermediate values in a calculation, such as in the calculation of WQBELs: as follows:

Table 6-5 ^[1]

				Hardne	ss (mg/l)						
Chloride (mg/l)	<100	100	150	200	250	300	350	400	450	500	>500
<5	500	500	500	500	500	500	500	500	500	500	500
5	500	515	703	891	1080	1268	1456	1644	1832	2020	2020
10	500	691	879	1067	1256	1444	1632	1820	2008	2196	2196
15	500	867	1055	1243	1432	1620	1808	1996	2184	2372	2372
20	500	1043	1231	1419	1608	1796	1984	2172	2360	2549	2549
25	500	1164	1343	1522	1701	1880	2059	2238	2417	2596	2596
50	500	1141	1320	1499	1678	1857	2036	2215	2394	2573	2573
100	500	1093	1272	1451	1630	1809	1988	2167	2346	2525	2525
150	500	1046	1225	1404	1583	1762	1941	2120	2299	2478	2478
200	500	998	1177	1356	1535	1715	1894	2073	2252	2431	2431

Date: Jan 27,2022 3:06:53PM EST DIN: 20211201-IR-327140058FRA

250 | 500 951 1130 1309 1488 1667 1846 2025 2204 2383 2383

^[1]The equations in clause (A) must be used instead of the criteria in this table when sulfate criteria are used as intermediate values in a calculation, such as in the calculation of WQBELs.

- (9) Fluoride must not exceed two (2.0) mg/l in surface waters outside of a mixing zone except in the Ohio River and Interstate Wabash River where it must not exceed one (1.0) mg/l outside of a mixing zone.
- (b) This subsection establishes minimum surface water quality for aquatic life. In addition to subsection (a), subdivisions (1) through (5) are established to ensure the following minimum conditions necessary for the maintenance of a well-balanced aquatic community. The following are applicable at any point in the surface waters outside of the a mixing zone to ensure conditions necessary for the maintenance of a well-balanced aquatic community:
 - (1) There shall must be no substances substance that:
 - (A) impart imparts unpalatable flavor to food fish; or
 - (B) result results in offensive odors in the vicinity of the water.
 - (2) No pH values below six (6.0) or above nine (9.0) are permitted, except daily fluctuations that:
 - (A) exceed pH nine (9.0); and
 - (B) are correlated with photosynthetic activity.

shall be permitted.

- (3) Concentrations of dissolved oxygen shall: must:
 - (A) average at least five (5.0) milligrams per liter per calendar day; and
 - (B) not be less than four (4.0) milligrams per liter at any time.
- (4) The following are Conditions for temperature are as follows:
 - (A) There shall be no Abnormal temperature changes that may adversely affect aquatic life **are prohibited** unless caused by natural conditions.
 - (B) The normal daily and seasonal temperature fluctuations that existed before the addition of heat due to other than natural causes shall **must** be maintained.
 - (C) The maximum temperature rise at any time or place above natural temperatures shall must not exceed:
 - (i) five (5) degrees Fahrenheit (two and eight-tenths (2.8) degrees Celsius) in streams; and
 - (ii) three (3) degrees Fahrenheit (one and seven-tenths (1.7) degrees Celsius) in lakes and reservoirs.
 - (D) Water temperatures shall must not exceed the maximum limits in the following table:
 - (i) during more than one percent (1%) of the hours in the twelve (12) month period ending with any month; At no time shall the water temperature at such locations exceed the maximum limits in the following table and
 - (ii) by more than three (3) degrees Fahrenheit (one and seven-tenths (1.7) degrees Celsius):

Table 6-4 **6-6**

	1 4516 (
	Ohio River Main Stem °F(°C)	Other Indiana Streams °F(°C)
January	50 (10.0)	50 (10.0)
February	50 (10.0)	50 (10.0)
March	60 (15.6)	60 (15.6)
April	70 (21.1)	70 (21.1)
May	80 (26.7)	80 (26.7)
June	87 (30.6)	90 (32.2)
July	89 (31.7)	90 (32.2)
August	89 (31.7)	90 (32.2)
September	87 (30.7)	90 (32.2)
October	78 (25.6)	78 (25.5)
November	70 (21.1)	70 (21.1)
December	57 (14.0)	57 (14.0)

- (5) The following criteria will must be used to regulate ammonia:
 - (A) Except for waters covered in clause (B), at all times, all surface waters outside of mixing zones shall must be free of substances in concentrations that, on the basis of available scientific data, are believed to be sufficient to (ii) injure, (iii) be chronically toxic to, or (iiii) be carcinogenic, mutagenic, or teratogenic to:

- (i) humans:
- (ii) animals;
- (iii) aquatic life; or

(iv) plants.

(B) For those waters listed in subsection (c), the following ammonia criteria will apply outside the of a mixing zone:

Table 6-7

Maximum Ammonia Concentrations (Unionized Ammonia as N)***

(mg/l) Temperature (°C)

			(mg/i) remp	erature (C)			
рН	0	5	10	15	20	25	30
6.5	0.0075	0.0106	0.0150	0.0211	0.0299	0.0299	0.0299
6.6	0.0092	0.0130	0.0183	0.0259	0.0365	0.0365	0.0365
6.7	0.0112	0.0158	0.0223	0.0315	0.0444	0.0444	0.0444
6.8	0.0135	0.0190	0.0269	0.0380	0.0536	0.0536	0.0536
6.9	0.0161	0.0228	0.0322	0.0454	0.0642	0.0642	0.0642
7.0	0.0191	0.0270	0.0381	0.0539	0.0761	0.0761	0.0761
7.1	0.0244	0.0316	0.0447	0.0631	0.0892	0.0892	0.0892
7.2	0.0260	0.0367	0.0518	0.0732	0.1034	0.1034	0.1034
7.3	0.0297	0.0420	0.0593	0.0837	0.1183	0.1183	0.1183
7.4	0.0336	0.0474	0.0669	0.0946	0.1336	0.1336	0.1336
7.5	0.0374	0.0528	0.0746	0.1054	0.1489	0.1489	0.1489
7.6	0.0411	0.0581	0.0821	0.1160	0.1638	0.1638	0.1638
7.7	0.0447	0.0631	0.0892	0.1260	0.1780	0.1780	0.1780
7.8	0.0480	0.0678	0.0958	0.1353	0.1911	0.1911	0.1911
7.9	0.0510	0.0720	0.1017	0.1437	0.2030	0.2030	0.2030
8.0	0.0536	0.0758	0.1070	0.1512	0.2135	0.2135	0.2135
8.1	0.0537	0.0758	0.1071	0.1513	0.2137	0.2137	0.2137
8.2	0.0537	0.0758	0.1071	0.1513	0.2137	0.2137	0.2137
8.3	0.0537	0.0758	0.1071	0.1513	0.2137	0.2137	0.2137
8.4	0.0537	0.0758	0.1071	0.1513	0.2137	0.2137	0.2137
8.5	0.0537	0.0758	0.1071	0.1513	0.2137	0.2137	0.2137
8.6	0.0537	0.0758	0.1071	0.1513	0.2137	0.2137	0.2137
8.7	0.0537	0.0758	0.1071	0.1513	0.2137	0.2137	0.2137
8.8	0.0537	0.0758	0.1071	0.1513	0.2137	0.2137	0.2137
8.9	0.0537	0.0758	0.1071	0.1513	0.2137	0.2137	0.2137
9.0	0.0537	0.0758	0.1071	0.1513	0.2137	0.2137	0.2137
							nk o nH

^{***}To calculate total ammonia, divide the number in the this table by the value determined by: $1/(10^{pK \text{ a -}pH} + 1)$.

Where: $pK_a = 0.09018 + (2729.92/(T + 273.2))$

pH = pH of water

 $T = {}^{\circ}C$

Table 6-8
24-Hour Average Ammonia Concentrations (Unionized Ammonia as N)***
(mg/l) Temperature (°C)

pН	0	5	10	15	20	25	30
6.5	0.0005	0.0008	0.0011	0.0015	0.0015	0.0015	0.0015
6.6	0.0007	0.0010	0.0014	0.0019	0.0019	0.0019	0.0019
6.7	0.0009	0.0012	0.0017	0.0024	0.0024	0.0024	0.0024
6.8	0.0011	0.0015	0.0022	0.0031	0.0031	0.0031	0.0031
6.9	0.0014	0.0019	0.0027	0.0038	0.0038	0.0038	0.0038
7.0	0.0017	0.0024	0.0034	0.0048	0.0048	0.0048	0.0048
7.1	0.0022	0.0031	0.0043	0.0061	0.0061	0.0061	0.0061
7.2	0.0027	0.0038	0.0054	0.0077	0.0077	0.0077	0.0077
7.3	0.0034	0.0048	0.0068	0.0097	0.0097	0.0097	0.0097
7.4	0.0043	0.0061	0.0086	0.0122	0.0122	0.0122	0.0122
7.5	0.0054	0.0077	0.0108	0.0153	0.0153	0.0153	0.0153

Date: Jan 27,2022 3:06:53PM EST DIN: 20211201-IR-327140058FRA Page 16

7.6	0.0068	0.0097	0.0136	0.0193	0.0193	0.0193	0.0193
7.7	0.0086	0.0122	0.0172	0.0242	0.0242	0.0242	0.0242
7.8	0.0092	0.0130	0.0184	0.0260	0.0260	0.0260	0.0260
7.9	0.0098	0.0138	0.0196	0.0276	0.0276	0.0276	0.0276
8.0	0.0103	0.0146	0.0206	0.0294	0.0294	0.0294	0.0294
8.1	0.0103	0.0146	0.0206	0.0294	0.0294	0.0294	0.0294
8.2	0.0103	0.0146	0.0206	0.0294	0.0294	0.0294	0.0294
8.3	0.0103	0.0146	0.0206	0.0294	0.0294	0.0294	0.0294
8.4	0.0103	0.0146	0.0206	0.0294	0.0294	0.0294	0.0294
8.5	0.0103	0.0146	0.0206	0.0294	0.0294	0.0294	0.0294
8.6	0.0103	0.0146	0.0206	0.0294	0.0294	0.0294	0.0294
8.7	0.0103	0.0146	0.0206	0.0294	0.0294	0.0294	0.0294
8.8	0.0103	0.0146	0.0206	0.0294	0.0294	0.0294	0.0294
8.9	0.0103	0.0146	0.0206	0.0294	0.0294	0.0294	0.0294
9.0	0.0103	0.0146	0.0206	0.0294	0.0294	0.0294	0.0294

^{***}To calculate total ammonia, divide the number in the this table by the value determined by: 1/(10^{pK a -pH} + 1).

Where: $pK_a = 0.09018 + (2729.92/(T + 273.2))$

pH = pH of water

 $T = ^{\circ}C$

- (c) This subsection establishes surface water quality Waters designated by the Indiana department of natural resources for put-and-take trout fishing are designated as salmonid waters and must be protected for cold-water fish. In addition to subsections (a) and (b), the following criteria are established to ensure conditions necessary for the maintenance of a well-balanced, cold-water fish community and are applicable at any point in the waters outside of the a mixing zone in the surface waters designated as salmonid waters to ensure conditions necessary for the maintenance of a well-balanced, cold-water fish community:
 - (1) Waters:
 - (A) designated as salmonid waters; and
 - (B) that shall be protected for cold-water fish;

are those waters designated by the Indiana department of natural resources for put and take trout fishing.

- (2) In the waters listed in subdivision (1),
- (1) Dissolved oxygen concentrations shall must not be less than:
 - (A) six (6.0) milligrams per liter at any time; and
 - (B) seven (7.0) milligrams per liter in areas where spawning occurs during the spawning season and in areas used for imprinting during the time salmonids are being imprinted.
- (3) In those waters listed in subdivision (1), (2) The maximum temperature rise above natural shall must not exceed two (2) degrees Fahrenheit (one and one-tenth (1.1) degrees Celsius) at any time or place and, unless due to natural causes, the temperature shall must not exceed the following:
 - (A) Seventy (70) degrees Fahrenheit (twenty-one and one-tenth (21.1) degrees Celsius) at any time.
 - (B) Sixty-five (65) degrees Fahrenheit (eighteen and three-tenths (18.3) degrees Celsius) during spawning and imprinting periods.
- (d) This subsection establishes Bacteriological quality for recreational uses during the recreational season **is** as follows:
 - (1) The recreational season is defined as the months of April through October, inclusive.
 - (2) In addition to subsection (a), the criteria in this subsection are to be used to do the following:
 - (A) Evaluate waters for full body contact recreational uses.
 - (B) Establish wastewater treatment requirements.
 - (C) Establish effluent limits during the recreational season.
 - (3) For full body contact recreational uses, E. coli bacteria shall must not exceed the following:
 - (A) One hundred twenty-five (125) **colony forming units (cfu) or most probable number (MPN)** per one hundred (100) milliliters as a geometric mean based on not less than five (5) samples equally spaced over a thirty (30) day period.
 - (B) Two hundred thirty-five (235) **cfu or MPN** per one hundred (100) milliliters in any one (1) sample in a thirty (30) day period, except that, in cases where there are at least ten (10) samples at a given site, up to ten percent (10%) of the samples may exceed two hundred thirty-five (235) cfu or MPN per one hundred (100) milliliters where the:

(i) E. coli exceedances are incidental and attributable solely to E. coli resulting from the discharge of treated wastewater from a wastewater treatment plant as defined at <u>IC 13-11-2-258</u>; and (ii) criterion in clause (A) is met.

However, a single sample shall be is used for making beach notification and closure decisions.

- If a geometric mean cannot be calculated because five (5) equally spaced samples are not available, then the criterion stated in clause (B) must be met.
- (4) For demonstrating compliance with wastewater treatment requirements, sanitary wastewater dischargers shall ensure the following:
 - (A) The concentration of E. coli in the undiluted discharge does not exceed one hundred twenty-five (125) cfu or MPN per one hundred (100) milliliters as a geometric mean of the effluent samples taken in a calendar month.
 - (B) Not more than ten percent (10%) of all samples when not less than ten (10) samples are taken and analyzed for E. coli in a calendar month exceed two hundred thirty-five (235) cfu or MPN per one hundred (100) milliliters as a daily maximum. Under this clause, the calculation of ten percent (10%) of the samples taken shall must be limited to the lowest whole number result.
- (5) Effluent limits to implement the criteria in subdivision (3) during the recreational season shall **must** be established in NPDES permits by incorporating the following that are to be applied to the undiluted discharge:
 - (A) The concentration of E. coli in the undiluted discharge shall must not exceed one hundred twenty-five (125) cfu or MPN per one hundred (100) milliliters as a geometric mean of the effluent samples taken in a calendar month.
 - (B) Not more than ten percent (10%) of all samples in a calendar month exceed two hundred thirty-five (235) cfu or MPN per one hundred (100) milliliters as a daily maximum. Under this clause, the calculation of ten percent (10%) of the samples taken shall **must** be limited to the lowest whole number result.
- (e) This subsection establishes surface water quality for public water supply. In addition to subsections (a) and (d), the following criteria are established to protect the surface water quality at the point at which water is withdrawn for treatment for public water supply are as follows:
 - (1) The coliform bacteria group shall must not exceed the following:
 - (A) Five thousand (5,000) **cfu or MPN** per one hundred (100) milliliters as a monthly average value (either MPN or **membrane filter** (MF) count).
 - (B) Five thousand (5,000) **cfu or MPN** per one hundred (100) milliliters in more than twenty percent (20%) of the samples examined during any month.
 - (C) Twenty thousand (20,000) **cfu or MPN** per one hundred (100) milliliters in more than five percent (5%) of the samples examined during any month.
 - (2) Taste and odor producing substances, other than naturally occurring, shall must not interfere with the production of a finished water by conventional treatment consisting of the following:
 - (A) Coagulation.
 - (B) Sedimentation.
 - (C) Filtration.
 - (D) Disinfection.
 - (3) The concentrations of either chloride or sulfate shall must not exceed two hundred fifty (250) milligrams per liter unless due to naturally occurring sources.
 - (4) The concentration of dissolved solids shall must not exceed seven hundred fifty (750) milligrams per liter unless due to naturally occurring sources. A specific conductance of one thousand two hundred (1,200) micromhos per centimeter (at twenty-five (25) degrees Celsius) may be considered equivalent to a dissolved solids concentration of seven hundred fifty (750) milligrams per liter.
 - (5) Surface waters shall be considered **are** acceptable for public water supply if radium-226 and strontium-90 are present in amounts not exceeding three (3) and ten (10) picocuries per liter, respectively. In the known absence of strontium-90 and alpha emitters, the water supply is acceptable when the gross beta concentrations do not exceed one thousand (1,000) picocuries per liter.
 - (6) The:
 - (A) combined concentration of nitrate-N and nitrite-N must not exceed ten (10) milligrams per liter as a thirty (30) day average value; and
 - (B) concentration of nitrite-N must not exceed one (1) milligram per liter as a thirty (30) day average value.
 - (6) (7) Chemical constituents in the waters shall must not be present in such at levels as to that prevent, after conventional treatment, meeting the drinking water standards contained in 327 IAC 8-2, due to other than natural causes.
 - (f) This subsection establishes surface water quality for industrial water supply. In addition to subsection (a),

the criterion to ensure protection of water quality at the point at which water is withdrawn for use (either with or without treatment) for industrial cooling and processing is that, other than from naturally occurring sources, the dissolved solids shall must not exceed seven hundred fifty (750) milligrams per liter at any time other than from naturally occurring sources to ensure protection of water quality at the point at which surface water is withdrawn for use, either with or without treatment, for industrial cooling and processing. A specific conductance of one thousand two hundred (1,200) micromhos per centimeter (at twenty-five (25) degrees Celsius) may be considered equivalent to a dissolved solids concentration of seven hundred fifty (750) milligrams per liter.

- (g) This subsection establishes surface water quality for agricultural uses. The criteria to ensure **surface** water quality conditions necessary for agricultural use are the same as those in subsection (a).
- (h) This subsection establishes surface water quality for limited uses. The quality of surface waters elassified designated for limited uses under section 3(a)(5) 11(a) of this rule shall, must, at a minimum, meet the following criteria (1) The criteria contained in subsection subsections (a), (2) The criteria contained in subsection (d), (3) The criteria contained in subsection (f), and where applicable, (4) The waters must (f), and be aerobic at all times. (5) Notwithstanding subdivisions (1) through (4), the quality of a limited use stream However, the water must meet the criteria that are applicable to the higher use water at the point where it a limited use water:
 - (1) becomes physically or chemically capable of supporting a higher use; or at its interface
 - (2) interfaces with a higher use water segment. shall meet the criteria that are applicable to the higher use water.

*This document is incorporated by reference. Copies may be obtained from the U.S. EPA National Service Center for Environmental Publications (www.epa.gov/nscep), or are available for review at the Indiana Department of Environmental Management, Office of Legal Counsel, Indiana Government Center North, Thirteenth Floor, 100 North Senate Avenue, Indianapolis, Indiana 46204.

(Water Pollution Control Division; <u>327 IAC 2-1-6</u>; filed Sep 24, 1987, 3:00 p.m.: 11 IR 581; filed Feb 1, 1990, 4:30 p.m.: 13 IR 1020; errata, 13 IR 1861; errata filed Jul 6, 1990, 5:00 p.m.: 13 IR 2003; filed Feb 26, 1993, 5:00 p.m.: 16 IR 1725; errata filed May 7, 1993, 4:00 p.m.: 16 IR 2189; filed Jan 14, 1997, 12:00 p.m.: 20 IR 1348; errata filed Aug 11, 1997, 4:15 p.m.: 20 IR 3376; filed Feb 14, 2005, 10:05 a.m.: 28 IR 2047; errata filed Apr 6, 2006, 2:48 p.m.: 29 IR 2546; errata, 29 IR 3027; filed Mar 18, 2008, 2:26 p.m.: <u>20080416-IR-327060573FRA</u>; filed May 22, 2008, 10:40 a.m.: <u>20080618-IR-327070185FRA</u>; filed Jul 9, 2012, 2:54 p.m.: <u>20120808-IR-327110320FRA</u>; filed Nov 10, 2014, 1:51 p.m.: <u>20141210-IR-327130290FRA</u>; filed Nov 5, 2021, 12:56 p.m.: <u>20211201-IR-327140058FRA</u>)

SECTION 2. 327 IAC 2-1.5-8 IS AMENDED TO READ AS FOLLOWS:

327 IAC 2-1.5-8 Minimum surface water quality criteria

Authority: IC 13-14-8-2; IC 13-14-8-3; IC 13-18-4-3

Affected: IC 13-11-2-258; IC 13-18-4; IC 13-30-2-1; IC 14-22-9

Sec. 8. (a) All surface water quality criteria in this section, except those provided in subsection (b)(1), will cease to be are not applicable when the stream flows are less than the applicable stream design flow for the particular criterion as determined under 327 IAC 5-2-11.4.

- (b) The following are minimum surface water quality conditions:
- (1) All surface waters within the Great Lakes system, at all times, and at all places, including waters within the a mixing zone, shall meet the minimum conditions of being must be free from substances, materials, floating debris, oil, or scum attributable to municipal, industrial, agricultural, and other land use practices, or other discharges that do any of the following:
 - (A) Will Settle to form putrescent or otherwise objectionable deposits.
 - (B) Are Occur in amounts sufficient to be unsightly or deleterious.
 - (C) Produce:
 - (i) color;
 - (ii) visible oil sheen;
 - (iii) odor; or
 - (iv) other conditions;

in such degree as to create an extent that creates a nuisance.

- (D) Are **Occur** in concentrations or combinations that will cause or contribute to the growth of aquatic plants or algae to such a degree as to:
- (i) create a nuisance;
- (ii) be unsightly; or
- (iii) otherwise impair the designated uses of the surface waters.
- (E) Are Occur in amounts sufficient to be acutely toxic to, or to otherwise severely injure or kill, aquatic life, other animals, plants, or humans. To assure ensure protection of aquatic life, the surface waters shall must meet the following requirements:
- (i) Concentrations of toxic substances shall must not exceed the CMC or SMC outside the zone of initial dilution or the final acute value (FAV = 2 (CMC) or 2 (SMC)) in the undiluted discharge unless, for a discharge to a receiving stream or Lake Michigan, an alternate mixing zone demonstration is conducted and approved in accordance with 327 IAC 5-2-11.4(b)(4), in which case, the CMC or SMC shall must be met outside the applicable alternate mixing zone. The following apply where applicable:
 - (AA) For certain substances, a CMC is established and set forth specified in:
 - (aa) subdivision (3), Table 8-1, which table incorporates subdivision (4), Table 8-2; and (bb) subdivision (5).
 - (BB) For substances for which a CMC is not specified in subdivision (3), Table 8-1, **subdivision (4)**, **Table 8-2**, or subdivision (5):
 - (aa) a CMC shall must be calculated by the commissioner using the procedures in section 11 of this rule; or
 - **(bb)** if the minimum data requirements to calculate a CMC are not met, an SMC shall must be calculated using the procedures in section 12 of this rule. and
- (CC) The CMC or SMC determined under subitem (AA) or (BB) may be modified on a site-specific basis to reflect local conditions in accordance with section 16 of this rule.
- (ii) A discharge shall **must** not cause acute toxicity, as measured by whole effluent toxicity tests, at any point in the waterbody. Compliance with this criterion shall be **is** demonstrated if a discharge does not exceed one and zero-tenths (1.0) TU in the undiluted discharge. For a discharge into a receiving stream or Lake Michigan, for which an alternate mixing zone demonstration is conducted and approved in accordance with 327 IAC 5-2-11.4(b)(4), compliance with this criterion shall be **is** demonstrated if three-tenths (0.3) TU is not exceeded outside the applicable alternate mixing zone. This
- **(F)** Clause shall **(E)** does not apply to the chemical control of plants and animals when that control is performed in compliance with approval conditions specified by the Indiana department of natural resources as provided by IC 14-22-9.
- (2) At All times, all surface waters outside of the applicable mixing zones determined in accordance with section 7 of this rule shall must be free of substances in concentrations that, on the basis of available scientific data, are believed to be sufficient to injure, be chronically toxic to, or be carcinogenic, mutagenic, or teratogenic to humans, animals, aquatic life, or plants. To assure ensure protection against the adverse effects identified in this subdivision, a toxic substance or pollutant shall must not be present in such surface waters outside of the applicable mixing zones determined in accordance with section 7 of this rule in concentrations that exceed the most stringent of the following:
 - (A) A CCC or an SCC to protect aquatic life from chronic toxic effects, which is determined as follows:
 - (i) For certain substances, a CCC is established and set forth specified in:
 - (AA) subdivision (3), Table 8-1, which table incorporates subdivision (4), Table 8-2;
 - (BB) subdivision (3), Table 8-1a; and
 - (CC) subdivision (5).
 - (ii) For substances for which a CCC is not specified in subdivision (3), Table 8-1, **subdivision (3)**, **Table 8-1a**, **subdivision (4)**, **Table 8-2**, or subdivision (5):
 - (AA) a CCC shall must be calculated by the commissioner using the procedures in section 11 of this rule; or
 - **(BB)** if the minimum data requirements to calculate a CCC are not met, an SCC shall must be calculated using the procedures in section 12 of this rule.
 - (iii) The CCC or SCC determined under item (i) (i)(AA), (i)(CC), or (ii) may be modified on a site-specific basis to reflect local conditions in accordance with section 16 of this rule.
 - (iv) To assure ensure protection of aquatic life, a discharge shall must not cause chronic toxicity, as measured by whole effluent toxicity tests, outside of the applicable mixing zone. Compliance with this criterion shall be is demonstrated if the waterbody does not exceed one and zero-tenths (1.0) TU_c at the edge of the mixing zone.
 - (B) An HNC or HNV to protect human health from adverse noncancer effects that may result from the consumption of aquatic organisms or drinking water from the waterbody, **which is** determined as follows:
 - (i) For certain substances, an HNC is established and set forth specified in subdivision (6), Table 8-3.

- (ii) For substances for which an HNC is not specified in subdivision (6), Table 8-3:
- (AA) an HNC shall must be calculated by the commissioner using the procedures in section 14 of this rule; or
- (BB) if the minimum data requirements to calculate an HNC are not met, an HNV shall must be calculated using the procedures in section 14 of this rule.
- (iii) The HNC or HNV determined under item (i) or (ii) may be modified on a site-specific basis to reflect local conditions in accordance with section 16 of this rule.
- (iv) The HNC for nondrinking water or HNV for nondrinking water for a substance shall apply applies to all surface waters outside the applicable mixing zone for a discharge of that substance. The HNC for drinking water or HNV for drinking shall apply water for a substance applies at the point of the public water system intake.
- (C) For carcinogenic substances, an HCC or HCV to protect human health from unacceptable cancer risk of greater than one (1) additional occurrence of cancer per one hundred thousand (100,000) population, which is determined as follows:
- (i) For certain substances, an HCC is established and set forth specified in subdivision (6), Table 8-3.
- (ii) For substances for which an HCC is not specified in subdivision (6), Table 8-3:
- (AA) an HCC shall must be calculated by the commissioner using the procedures in section 14 of this rule; or
- (BB) if the minimum data requirements to calculate an HCC are not met, an HCV shall must be calculated using the procedures in section 14 of this rule.
- (iii) The HCC or HCV determined under item (i) or (ii) may be modified on a site-specific basis to reflect local conditions in accordance with section 16 of this rule.
- (iv) The HCC for nondrinking water or HCV for nondrinking water for a substance shall apply applies to all surface waters outside the applicable mixing zone for a discharge of that substance. The HCC for drinking water or HCV for drinking shall apply water applies at the point of the public water system intake.
- (D) A WC to protect avian and mammalian wildlife populations from adverse effects that may result from the consumption of aquatic organisms or water from the waterbody, which is determined as follows:
- (i) For certain substances, a WC is established and set forth specified in subdivision (7), Table 8-4.
- (ii) For substances for which a WC is not specified in subdivision (7), Table 8-4:
- (AA) a WC shall must be calculated by the commissioner using the procedures in section 15 of this rule; or
- (BB) if the minimum data requirements to calculate a WC are not met, a WV may be calculated using the procedures in section 15 of this rule.
- (iii) The WC or WV determined under item (i) or (ii) may be modified on a site-specific basis to reflect local conditions in accordance with section 16 of this rule.
- (3) The following establishes Surface water quality criteria for protection of aquatic life are as follows:

Table 8-1 Surface Water Quality Criteria for Protection of Aquatic Life^[1]

CAS Number	Substances Metals (dissolved) ^[2]	CMC (Maximum) (µg/l)	CMC Conversion Factors	CCC (4-Day Average) (µg/l)	CCC Conversion Factors
7440382	Arsenic (III)	WER ^[3] (339.8)	1.000	WER ^[3] (147.9)	1.000
7440439	Cadmium	WER ^[3] (e ^{(1.128} [In(hardness)] 3.6867))	1.136672-[(In hardness) (0.041838)]	WER ^[3] (e ^{(0.7852} [In(hardness)] 2.715))	1.101672 [(In hardness) (0.041838)]
7440473	Chromium (III)	WER ^[3] (e ^{(0.819} [In(hardness)] + 3.7256))	0.316	WER ^[3] (e ^{(0.819} [In(hardness)] + 0.6848))	0.860
7440473	Chromium (VI)	WER ^[3] (16.02)	0.982	WER ^[3] (10.98)	0.962
7440508	Copper	WER ^[3] (e ^{(0.9422} [In(hardness)] 1.700))	0.960	WER ^[3] (e ^{(0.8545} [In(hardness)] 1.702))	0.960

	3				
7439976	Mercury	WER ^[3] (1.694)	0.85	WER ^[3] (0.9081)	0.85
7440020	Nickel	WER ^[3] (e ^{(0.846}	0.998	WER ^[3] (e ^{(0.846}	0.997
		[In(hardness)] +		[In(hardness)] + 0.0584)	
		2.255))			
7782492	Selenium			5	0.922
7440666	Zinc	WER ^[3] (e ^{(0.8473}	0.978	WER ^[3] (e ^{(0.8473}	0.986
		[In(hardness)] +		[In(hardness)] + 0.884)	
		0.884))			
	Organics (total)				
60571	Dieldrin	0.24	NA	0.056	NA
72208	Endrin	0.086	NA	0.036	NA
56382	Parathion	0.065	NA	0.013	NA
87865	Pentachlorophenol [4][6]	e ^(1.005[pH]-4.869)	NA	e ^(1.005[pH]-5.134)	NA
	Other Substances				
	Chloride	[6]	NA	[6]	NA
	Chlorine (total residual)	19	NA	11	NA
	Chlorine (intermittent,	200	NA		NA
	total-residual) ^[5]				
57125	Cyanide (free)	22	NA	5.2	NA

^[11] Aquatic organisms should not be affected unacceptably if the four (4) day average concentration of any substance in this table does not exceed the CCC more than once every three (3) years on the average and if the one (1) hour average concentration does not exceed the CMC more than once every three (3) years on the average, except possibly where a commercially or recreationally important species is very sensitive.

(A) The surface water quality criteria for the protection of aquatic life for specific substances are as follows:

	Table 8-1									
	Surface Water Quality Criteria for Protection of Aquatic Life									
CAS Number	Substances	Criterion Maximum Concentration (CMC) (Maximum) (µg/L) ^[1]	CMC Conversion Factors (CF)	Criterion Continuous Concentration (CCC) (4-Day Average) (µg/L) ^[1]	CCC Conversion Factors (CF)					
Metals (diss	Metals (dissolved) ^{[2][3]}									
7440382	Arsenic	WER(340)(CF)	1.000	WER(150)(CF)	1.000					

^[2]The CMC and CCC columns of this table contain total recoverable metals criteria (numeric and hardness-based). The criterion for the dissolved metal is calculated by multiplying the appropriate conversion factor by the CMC or CCC. This dissolved CMC or CCC shall be rounded to two (2) significant digits, except when the criteria are used as intermediate values in a calculation, such as in the calculation of water quality-based effluent limitations (WQBELs).

^[3] A value of one (1) shall be used for the WER unless an alternate value is established under section 16 of this rule.

^[4]A CMC and CCC calculated for pentachlorophenol using the equation in this table shall be rounded to two (2) significant digits, except when the criteria are used as intermediate values in a calculation, such as in the calculation of WQBELs.

^[6] To be considered an intermittent discharge, total residual chlorine shall not be detected in the discharge for a period of more than forty (40) minutes in duration, and such periods shall be separated by at least five (5) hours.

[6] The CMC and CCC for this substance are established in subdivision (5).

7440439	Cadmium	WER (e ^{(0.9789 [InH] -} ^{3.866)})(CF)	1.136672 - [InH] 0.041838	WER (e ^{(0.7977[InH]} - 3.909))(CF)	1.101672 - [ln H]0.041838
7440473	Chromium (III)	WER (e ^{(0.819 [InH] +} 3.7256))(CF)	0.316	WER (e ^{(0.819 [InH] +} 0.6848))(CF)	0.860
7440473	Chromium (VI)	WER(16)(CF)	0.982	WER(11)(CF)	0.962
7440508	Copper	WER (e ^{(0.9422[InH] -} 1.700))(CF)	0.960	WER (e ^{(0.8545[InH]} - 1.702))(CF)	0.960
7439921	Lead	WER (e ^{(1.273[InH]} - 1.460))(CF)	1.46203 - [InH]0.145712	WER (e ^{(1.273[InH]} - 4.705))(CF)	1.46203 - [lnH]0.145712
7439976	Mercury	WER(1.694)(CF)	0.85	WER(0.9081)(CF)	0.85
7440020	Nickel	WER (e ^{(0.846 [InH] +} ^{2.255)})(CF)	0.998	WER (e ^{(0.846 [InH] +} 0.0584))(CF)	0.997
7440666	Zinc	WER (e ^{(0.8473 [InH]} + 0.884))(CF)	0.978	WER (e ^{(0.8473 [InH] +} 0.884))(CF)	0.986
rganics (T	otal)		-		
60571	Dieldrin	0.24	NA	0.056	NA
72208	Endrin	0.086	NA	0.036	NA
56382	Parathion	0.065	NA	0.013	NA
87865	Pentachlorophenol ^[4]	e ^(1.005[pH] - 4.869)	NA	e ^(1.005[pH] - 5.134)	NA
ther Subst	ances				
	Chlorine (total residual)	19	NA	11	NA
	Chlorine (intermittent, total residual) ^[5]	200	NA		NA
57125	Cyanide (free)	22	NA	5.2	NA
elenium C	CC are specified in clause	e (B)	•		

^[1] Aquatic organisms should not be affected unacceptably if the four (4) day average concentration specified in this table for a substance does not exceed the CCC more than once every three (3) years on the average and if the one (1) hour average concentration does not exceed the CMC more than once every three (3) years on the average, except possibly where a commercially or recreationally important species is very sensitive.

^[3]The hardness values used in the equations for these criteria must not be greater than 400 mg/l as calcium carbonate (CaCO₃), and the criteria at a hardness of 400 mg/l as CaCO₃ are used for a water hardness above 400 mg/l as CaCO₃. The term "InH" is the natural log of hardness.

(B) The surface water quality criterion for the protection of aquatic life for selenium is as follows:

	Table 8-1a						
	Surface Water Qu	uality Aquatic Life	Criterion for Seler	nium (CAS # 7782492)			
	Criterion Continuous Concentration (CCC)						
Media Type	Fish Ti	issue ^[1]		Water Column ^{[5][7]}			
Criterion Element	Egg/Ovary ^[2]	Fish Whole-Body or	Monthly Average	Intermittent Exposure ^[6]			

^[2]Aquatic life criteria for these metals are expressed as a dissolved concentration and are calculated using the water-effect ratio (WER) and the specified conversion factor (CF). The CMC and CCC for a dissolved metal are calculated by multiplying the WER by the criterion value or formula and then by the appropriate CF. A value of one (1) must be used for the WER unless an alternate value is established under section 16 of this rule. The dissolved CMC and CCC must be rounded to two (2) significant digits, except when the criteria are used as intermediate values in a calculation, such as in the calculation of water quality-based effluent limitations (WQBELs).

^[4]A CMC and CCC calculated for pentachlorophenol using the equation in this table must be rounded to two (2) significant digits, except when the criteria are used as intermediate values in a calculation, such as in the calculation of WQBELs.

^[5] To be considered an intermittent discharge, total residual chlorine must not be detected in the discharge for a period of more than forty (40) minutes in duration, and these time periods must be separated by at least five (5) hours.

		Muscle ^[3]	Exposure	
Magnitude	15.1 mg/kg dw	8.5 mg/kg dw whole-body or 11.3 mg/kg dw muscle (skinless, boneless filet)	1.5 µg/l in lentic aquatic systems 3.1 µg/l in lotic aquatic systems	$WQC_{ m int} =$ $WQC_{ m 30-day} - C_{ m bkgrnd}(1-f_{ m int})$
				$f_{ m int}$
Duration	Instantaneous measurement ^[4]	Instantaneous measurement ^[4]	Thirty (30) days	Number of days per month with an elevated concentration
Frequency	Not to be exceeded	Not to be exceeded	Not more than once in three (3) years on average	Not more than once in three (3) years on average

^[1] Fish tissue elements are expressed as steady-state; the aquatic system should not be experiencing new or increasing inputs of selenium.

^[4]Fish tissue data provide instantaneous point measurements that reflect integrative accumulation of selenium over time and space in fish populations at a given site.

[5]Water column values are the applicable criterion element in the absence of steady-state condition fish tissue data and for fishless waters. Water column values are based on dissolved total selenium in water and are derived from fish tissue values via bioaccumulation modeling. Instead of the requirement in 327 <u>IAC 5-2-11.4(b)(3)(A)(i)(CC)</u>, the thirty (30) day, ten (10) year stream design flow ($Q_{30,10}$) must be used for deriving total maximum daily loads (TMDLs), waste load allocations (WLAs) in the absence of TMDLs, and preliminary WLAs for tributaries of the Great Lakes system that exhibit appreciable flows relative to their volumes for the CCC water column criterion element applicable to lotic aquatic systems unless data exist to demonstrate that an alternate stream design flow is appropriate for stream-specific and pollutant-specific conditions.

[6] Intermittent Exposure Equation variables mean the following:

WQC is the water column intermittent element.

 WQC_{30-day}^{int} is the water column monthly element for either lentic or lotic waters. C_{bkgrnd}^{old} is the average background selenium concentration. f_{int}^{bkgrnd} is the fraction of any 30-day period during which elevated selenium concentrations occur, with f_{int}^{old} f int is the fraction of any 30-day period during which case int assigned a value ≥0.033 (corresponding to one (1) day).

^[7]The water column criterion element may be modified on a site-specific basis in accordance with clause

- (C) Modification of the selenium water column criterion element must be achieved according to the
- (i) Site-specific water column criterion elements must be derived using either the empirical bioaccumulation factor (BAF) or mechanistic modeling method provided in Aquatic Life Ambient Water Quality Criterion for Selenium - Freshwater, EPA-822-R-16-006, Appendix K: Translation of a Selenium Fish Tissue Criterion Element to a Site-Specific Water Column Value (June 2016)*.
- (ii) Any proposal to derive a site-specific water column criterion element must be submitted to the department for review and approval of the methodology and sampling plan prior to initiation of sampling. The department shall evaluate and approve the applicability of and use of all representative data used to derive a site-specific water column criterion element.
- (iii) Any proposal to derive a site-specific water column criterion element must be protective of

^[2]Egg or ovary supersedes any whole-body, muscle, or water column element when fish egg or ovary concentrations are measured. Any proposal to sample egg or ovary fish tissue must be submitted to the department for review and approval prior to initiation of sampling, and the department will evaluate all representative egg or ovary fish tissue data to determine compliance with this criterion element. [3] Fish whole-body or muscle tissue supersedes the water column element when both fish tissue and water concentrations are measured. Any proposal to sample fish whole-body or muscle tissue must be submitted to the department for review and approval prior to initiation of sampling, and the department will evaluate all representative fish whole-body or muscle tissue data to determine compliance with this criterion element.

downstream designated uses for aquatic life and human health.

- (iv) Upon receipt of an application for a site-specific water column criterion element, the department shall do the following:
- (ÅA) Publish on the department swebsite all pertinent information about the proposed site-specific modification.
- (BB) Provide notice and request comment on the application.
- (v) Upon approval of a site-specific water column criterion element, the department shall do the following:
- (AA) Publish a notice in the Indiana Register.
- (BB) Place on the department's website all pertinent information about the approved site-specific modification.
- (CC) Submit the site-specific modification to U.S. EPA for approval.
- (DD) If approved by U.S. EPA, incorporate the site-specific modification into the water quality standards during the next revision of the water quality standards.
- (vi) Site-specific modifications of this criterion must not be incorporated into a final NPDES permit or used for other Clean Water Act purposes until approved by U.S. EPA.
- (4) The following establishes dissolved CMCs CMC and CCCs CCC for certain metals at selected hardness values calculated from the equations and conversion factors in subdivision (3), Table 8-1 and using with a value of one (1) used for the WER where applicable, are as follows:

Table 8-2

Metals Concentrations in Micrograms Per Liter; Hardness in Milligrams Per Liter CaCO₃^[1]

	Arser	nic (III)	Cad	Cadmium Chromium (III)		um (III)	Chromium (VI)		Copper	
Hardness	CMC	CCC	CMC	CCC	CMC	CCC	CMC	CCC	CMC	CCC
50	340	150	2.0 0.94	1.3 0.43	320	42	16	11	7.0	5.0
100	340	150	4 .3 1.8	2.2 0.72	570	74	16	11	13	9.0
150	340	150	6.6 2.6	3.0 0.97	790	100	16	11	20	13
200	340	150	9.0 3.4	3.7 1.2	1,000	130	16	11	26	16
250	340	150	12 4.2	4.4 1.4	1,200	160	16	11	32	20
300	340	150	14 5.0	5.0 1.6	1,400	180	16	11	38	23
350	340	150	17 5.8	5.6 1.8	1,600	210	16	11	44	26
400	340	150	19 6.5	6.2 2.0	1,800	230	16	11	50	29
450	340	150	22	6.8	2,000	250	16	11	55	32
500	340	150	24	7.3	2,100	280	16	11	61	35

	Lead		Mer	cury	Nicl	kel	Sele	nium	Zi	nc
Hardness	CMC	CCC	CMC	CCC	CMC	CCC	CMC	CCC	CMC	CCC
50	30	1.2	1.4	0.77	260	29	_	4.6	65	66
100	65	2.5	1.4	0.77	470	52	-	4.6	120	120
150	100	3.9	1.4	0.77	660	73	-	4.6	170	170
200	140	5.3	1.4	0.77	840	93	_	4.6	210	210
250	170	6.7	1.4	0.77	1,000	110	-	4.6	250	260
300	210	8.1	1.4	0.77	1,200	130	-	4.6	300	300
350	240	9.5	1.4	0.77	1,400	150	_	4.6	340	340
400	280	11	1.4	0.77	1,500	170	-	4.6	380	380
450			1.4	0.77	1,700	190	_	4.6	420	420
500			1.4	0.77	1,800	200	_	4.6	460	460

^[1] The dissolved metals criteria in this table have been rounded to two (2) significant digits in accordance with subdivision (3), Table 8-1. The equations and conversion factors in subdivision (3), Table 8-1 shall must be used instead of the criteria in this table when dissolved metals these criteria are used as intermediate values in a calculation, such as in the calculation of WQBELs.

⁽⁵⁾ The following establishes Surface water quality criteria for chloride for protection of aquatic life are as follows:

⁽A) The following provides the CMC for chloride as a function of hardness (in mg/l as $CaCO_3$) and sulfate (in mg/l) in surface waters is calculated using the following formula:

C = 287.8 (hardness)^{0.20579} (sulfate)

Where: C = chloride CMC (maximum) in mg/l.

(B) The following provides the CCC for chloride as a function of hardness (in mg/l as CaCO₂) and sulfate (in mg/l) in surface waters is calculated using the following formula: $C = 177.87 \text{ (hardness)}^{0.205797} \text{ (sulfate)}^{-0.07452}$

Where: C = chloride CCC (4-Day Average) in mg/l.

- (C) The CMC and CCC for chloride calculated from the equations in this subdivision shall must be rounded to the nearest whole numbers, except when the criteria are used as intermediate values in a calculation, such as in the calculation of WQBELs.
- (D) The following establishes the CMC for chloride in mg/l at selected concentrations of hardness (in mg/l as CaCO_a) and sulfate with the understanding that the equation in clause (A) shall be used instead of the criteria in this clause when chloride criteria are used as intermediate values in a calculation, such as in the calculation of WQBELs: is as follows:

Table 8-2a^[1] Hardness (mg/l) Sulfate (mg/l)

(E) The following establishes the CCC for chloride in mg/l at selected concentrations of hardness (in mg/l as CaCO_a) and sulfate with the understanding that the equation in clause (B) shall be used instead of the criteria in this clause when chloride criteria are used as intermediate values in a calculation, such as in the calculation of WQBELs: is as follows:

Table 8-2b ^[1]										
	Hardness (mg/l)									
Sulfate (mg/l)	50	100	150	200	250	300	350	400	450	500
15	325	375	408	433	453	470	485	499	511	522
20	318	367	399	423	443	460	475	488	500	511
25	313	361	392	416	436	453	467	480	492	503
50	297	343	373	395	414	430	444	456	467	477
100	282	326	354	375	393	408	421	433	444	453
150	274	316	343	364	381	396	409	420	430	440
200	268	309	336	357	373	388	400	411	421	431
250	264	304	331	351	367	381	394	404	414	423
300	260	300	326	346	362	376	388	399	409	418
350	257	297	322	342	358	372	384	394	404	413
400	255	294	319	339	355	368	380	391	400	409
450	252	291	316	336	351	365	377	387	397	405
500	250	289	314	333	349	362	374	384	394	402

^[1] The equation in clause (B) must be used instead of the criteria in this table when chloride criteria are

Date: Jan 27,2022 3:06:53PM EST DIN: 20211201-IR-327140058FRA Page 26

^[1] The equation in clause (A) must be used instead of the criteria in this table when chloride criteria are used as intermediate values in a calculation, such as in the calculation of WQBELs.

used as intermediate values in a calculation, such as in the calculation of WQBELs.

(6) The following establishes Surface water quality criteria for protection of human health are as follows:

Table 8-3
Surface Water Quality Criteria for Protection of Human Health^[1]

CAS	0.1.1	Human Noncance Drinking Water	Nondrinking	Human Cancer Drinking Water	Nondrinking
Number	Substances	(µg/l)	Water (µg/l)	(µg/l)	Water (µg/l)
7439976	Metals (total recoverable) Mercury (including methylmercury)	0.0018	0.0018		
	Organics (total)				
71432	Benzene	19	510	12	310
57749	Chlordane	0.0014	0.0014	0.00025	0.00025
108907	Chlorobenzene	470	3,200		
50293	DDT	0.002	0.002	0.00015	0.00015
60571	Dieldrin	0.00041	0.00041	6.5×10^{-6}	6.5×10^{-6}
105679	2,4-dimethylphenol	450	8,700		
51285	2,4-dinitrophenol	55	2,800		
118741	Hexachlorobenzene	0.046	0.046	0.00045	0.00045
67721	Hexachloroethane	6	7.6	5.3	6.7
58899	Lindane	0.47	0.5		
75092	Methylene chloride	1,600	90,000	47	2600
1336363	PCBs (class)			6.8×10^{-6}	6.8×10^{-6}
1746016	2,3,7,8-TCDD (dioxin)	6.7×10^{-8}	6.7 × 10 ⁻⁸	8.6 × 10 ⁻⁹	8.6×10^{-9}
108883	Toluene	5,600	51,000		
8001352	Toxaphene	3,000	0.,000	6.8 × 10 ⁻⁵	6.8×10^{-5}
79016	Trichloroethylene			29	370
13010	Other Substances			23	310
57125	Cyanide (total)	600	48,000		
	Cyaniue (total) C and HCC are thirty (30) da		40,000		

^[1] The HNC and HCC are thirty (30) day average criteria.

Table 8-4
Surface Water Quality Criteria for Protection of Wildlife^[1]

CAS Number	Substances	Wildlife Criteria (µg/l)
	Metals (total recoverable)	
7439976	Mercury (including methylmercury)	0.0013
	Organics (total)	
50293	DDT and metabolites	1.1×10^{-5}
1336363	PCBs (class)	1.2×10^{-4}
1746016	2, 3, 7, 8-TCDD (dioxin)	3.1×10^{-9}
[1]		

^[1]The WC are thirty (30) day average criteria.

⁽⁷⁾ The following establishes Surface water quality criteria for protection of wildlife are as follows:

⁽c) This subsection establishes minimum surface water quality criteria for aquatic life. In addition to the criteria in subsection (b), this subsection ensures the following minimum conditions necessary for the maintenance of a well-balanced aquatic community. The following conditions are applicable at any point in the surface waters outside of the applicable mixing zone, as determined in accordance with section 7 of this rule, to ensure conditions necessary for the maintenance of a well-balanced aquatic community:

- (1) There shall must be no substances substance that:
 - (A) impart imparts unpalatable flavor to food fish; or
 - (B) result results in offensive odors in the vicinity of the water.
- (2) No pH values below six (6.0) or above nine (9.0) are permitted, except daily fluctuations that:
 - (A) exceed pH nine (9.0); and
 - (B) are correlated with photosynthetic activity.

shall be permitted.

- (3) Concentrations of dissolved oxygen shall: must:
 - (A) average at least five (5.0) milligrams per liter per calendar day; and
 - (B) not be less than four (4.0) milligrams per liter at any time.
- (4) The following are Conditions for temperature are as follows:
 - (A) There shall be no Abnormal temperature changes that may adversely affect aquatic life are prohibited unless caused by natural conditions.
 - (B) The normal daily and seasonal temperature fluctuations that existed before the addition of heat due to other than natural causes shall **must** be maintained.
 - (C) Water temperatures shall must not exceed the maximum limits in the following table:
 - (i) during more than one percent (1%) of the hours in the twelve (12) month period ending with any month; At no time shall the water temperature at such locations exceed the maximum limits in the following table and
 - (ii) by more than three (3) degrees Fahrenheit (one and seven-tenths (1.7) degrees Celsius):

Table 8-5
Maximum Instream Water Temperatures

Month	St. Joseph River Tributary to Lake Michigan Upstream of the Twin Branch Dam °F(°C)	All Other Indiana Streams in the Great Lakes System °F(°C)
January	50 (10)	50 (10)
February	50 (10)	50 (10)
March	55 (12.8)	60 (15.6)
April	65 (18.3)	70 (21.1)
May	75 (23.9)	80 (26.7)
June	85 (29.4)	90 (32.2)
July	85 (29.4)	90 (32.2)
August	85 (29.4)	90 (32.2)
September	84 (29.4)	90 (32.2)
October	70 (21.1)	78 (25.5)
November	60 (15.6)	70 (21.1)
December	50 (10)	57 (14.0)

- (D) The following temperature criteria shall apply to Lake Michigan:
- (i) In all receiving waters, the points of measurement normally shall must be in the first meter below the surface at such depths necessary to avoid thin layer surface warming due to extreme ambient air temperatures, but, where required to determine the true distribution of heated wastes and natural variations in water temperatures, measurements shall must be at a greater depth and at several depths as a thermal profile.
- (ii) There shall be no Abnormal temperature changes so as to be injurious to fish, wildlife, or other aquatic life, or the growth or propagation thereof, **are prohibited.** In addition, plume interaction with the bottom shall: **must**:
- (AA) be minimized: and
- (BB) not injuriously affect fish, shellfish, and wildlife spawning or nursery areas.
- (iii) The normal daily and seasonal temperature fluctuations that existed before the addition of heat shall must be maintained.
- (iv) At any time and at a maximum distance of a one thousand (1,000) foot arc inscribed from a fixed point adjacent to the discharge or as agreed upon by the commissioner and federal regulatory agencies, the following shall apply:
- (AA) The receiving water temperature shall **must** not be more than three (3) degrees Fahrenheit (one and seven-tenths (1.7) degrees Celsius) above the existing natural water temperature.
- (BB) Thermal discharges to Lake Michigan shall must comply with the following maximum temperature requirements:
- (aa) Thermal discharges to Lake Michigan shall must not raise the maximum temperature in the receiving water above those listed in the following table, except to the extent the permittee adequately

demonstrates that the exceedance is caused by the water temperature of the intake water:

Table 8-6
Maximum Water Temperatures

Maximum Water	remperatures
Month	°F(°C)
January	45 (7)
February	45 (7)
March	45 (7)
April	55 (13)
May	60 (16)
June	70 (21)
July	80 (27)
August	80 (27)
September	80 (27)
October	65 (18)
November	60 (16)
December	50 (10)

- (bb) If the permittee demonstrates that the intake water temperature is within three (3) degrees Fahrenheit below an applicable maximum temperature under subitem (aa), Table 8-6, then not more than a three (3) degree Fahrenheit exceedance of the maximum water temperature shall be is permitted.
- (v) The **following** facilities described as follows that discharge into the open waters of Lake Michigan shall be are limited to the amount essential for blowdown in the operation of a closed cycle cooling facility:
- (AA) All facilities that have new waste heat discharges exceeding a daily average of five-tenths (0.5) billion British thermal units **(Btu)** per hour. As used in this item, "new waste heat discharge" means a **any** discharge that had not begun operations as of February 11, 1972.
- (BB) All facilities with existing waste heat discharges that increase the quantity of waste heat discharged by more than a daily average of five-tenths (0.5) billion British thermal units **Btu** per hour.
- (vi) Water intakes shall must be designed and located to minimize entrainment and damage to desirable organisms. Requirements may vary depending upon local conditions, but, in general, intakes shall: must:
- (AA) have minimum water velocity; and
- (BB) not be located in spawning or nursery areas of important fishes.

Water velocity at screens and other exclusion devices shall also must be at a minimum.

- (vii) Discharges other than those now in existence shall be such that the on or before February 11, 1972, must not have thermal plumes do not that overlap or intersect.
- (viii) Facilities discharging more than a daily average of five-tenths (0.5) billion British thermal units Btu of waste heat shall: must:
- (AA) continuously record intake and discharge temperature and flow; and
- (BB) make those records available to the public or regulatory agencies upon request.
- (5) The following criteria shall must be used to regulate ammonia:
 - (A) Concentrations of total ammonia (as N) shall **must** not exceed the CMC outside the zone of initial dilution or the final acute value (FAV = 2 (CMC)) in the undiluted discharge unless, for a discharge to a receiving stream or Lake Michigan, an alternate mixing zone demonstration is conducted and approved in accordance with 327 IAC 5-2-11.4(b)(4), in which case, the CMC shall **must** be met outside the applicable alternate mixing zone. The CMC of total ammonia (as N) is determined using the following equation:

CMC =
$$\frac{(0.822)(0.52)(10^{(pk_a - pH)} + 1)}{(FT)(FPH)(2)}$$

Where: FT =
$$10^{0.03(20\text{-T})}$$

FPH = 1; when: $8 \le pH \le 9$; or $\frac{1 + 10^{(7.4 - pH)}}{1.25}$; when: $6.5 \le pH \le 8$
pK_a = $0.09018 + \frac{2729}{T + 273.2}$

T = Temperature in °C

(B) The CCC of total ammonia (as N) is determined using the following equation:

$$CCC = \frac{(0.822)(0.80)(10^{(pk_a - pH)} + 1)}{(FT)(FPH)(RATIO)}$$

Where: FT =
$$10^{0.03(20\text{-T})}$$

FPH = 1; when: $8 \le \text{pH} \le 9$; or $1 + 10^{(7.4 - \text{pH})}$; when: $6.5 \le \text{pH} \le 8$
RATIO = 13.5 ; when: $7.7 \le \text{pH} \le 9$; or $(20)(10^{(7.7 - \text{pH})})$; when: $6.5 \le \text{pH} \le 7.7$

$$pK_a = 0.09018 + \frac{2729}{T + 273.2}$$

$$T = \text{Temperature in °C}$$

(C) The use of the equations in clause (A) results in the following CMCs for total ammonia (as N) at different temperatures and pHs:

Table 8-7
Criterion Maximum Concentrations for Total Ammonia (as N) Temperature (°C)

pH	0	5	10	15	20	25	30
6.5	28.48	26.61	25.23	24.26	23.64	23.32	23.29
6.6	27.68	25.87	24.53	23.59	22.98	22.68	22.65
6.7	26.74	24.99	23.69	22.78	22.20	21.92	21.90
6.8	25.64	23.96	22.72	21.85	21.30	21.03	21.01
6.9	24.37	22.78	21.60	20.78	20.26	20.01	20.00
7.0	22.95	21.45	20.35	19.58	19.09	18.86	18.86
7.1	21.38	19.98	18.96	18.24	17.80	17.59	17.60
7.2	19.68	18.40	17.46	16.81	16.40	16.22	16.24
7.3	17.90	16.73	15.88	15.29	14.93	14.78	14.81
7.4	16.06	15.02	14.26	13.74	13.42	13.30	13.35
7.5	14.23	13.31	12.64	12.19	11.92	11.81	11.88
7.6	12.44	11.65	11.07	10.67	10.45	10.37	10.45
7.7	10.75	10.06	9.569	9.238	9.052	9.003	9.088
7.8	9.177	8.597	8.181	7.907	7.760	7.734	7.830
7.9	7.753	7.268	6.924	6.701	6.589	6.584	6.689
8.0	6.496	6.095	5.813	5.636	5.555	5.569	5.683
8.1	5.171	4.857	4.639	4.508	4.457	4.486	4.602
8.2	4.119	3.873	3.707	3.612	3.584	3.625	3.743
8.3	3.283	3.092	2.967	2.900	2.891	2.942	3.061
8.4	2.618	2.472	2.379	2.335	2.340	2.399	2.519
8.5	2.091	1.979	1.911	1.886	1.903	1.968	2.089
8.6	1.672	1.588	1.540	1.529	1.555	1.625	1.747
8.7	1.339	1.277	1.246	1.246	1.279	1.353	1.475
8.8	1.075	1.030	1.011	1.021	1.060	1.137	1.260
8.9	0.8647	0.8336	0.8254	0.8418	0.8862	0.9650	1.088
9.0	0.6979	0.6777	0.6777	0.6998	0.7479	0.8286	0.9521
(D) The	Luce of the equ	ationa in aloua	o (D) roculto in	the following	CCCo for total	ammonia (an I	Al) at different

(D) The use of the equations in clause (B) results in the following CCCs for total ammonia (as N) at different

temperatures and pHs:

Table 8-8
Criterion Continuous Concentrations for Total Ammonia (as N) Temperature (°C)

	Criterion Co	ontinuous Cond	centrations for	Total Ammonia	a (as N) Temp	erature (°C)	
pН	0	5	10	15	20	25	30
6.5	2.473	2.310	2.191	2.106	2.052	2.025	2.022
6.6	2.473	2.311	2.191	2.107	2.053	2.026	2.023
6.7	2.473	2.311	2.191	2.107	2.054	2.027	2.025
6.8	2.473	2.311	2.192	2.108	2.055	2.028	2.027
6.9	2.474	2.312	2.193	2.109	2.056	2.030	2.030
7.0	2.474	2.312	2.193	2.110	2.058	2.033	2.033
7.1	2.475	2.313	2.195	2.112	2.060	2.036	2.037
7.2	2.475	2.314	2.196	2.114	2.063	2.040	2.043
7.3	2.476	2.315	2.198	2.116	2.066	2.044	2.050
7.4	2.477	2.317	2.200	2.119	2.070	2.050	2.058
7.5	2.478	2.319	2.202	2.123	2.075	2.058	2.069
7.6	2.480	2.321	2.206	2.128	2.082	2.067	2.082
7.7	2.450	2.294	2.181	2.106	2.063	2.052	2.071
7.8	2.092	1.959	1.865	1.802	1.769	1.763	1.785
7.9	1.767	1.657	1.578	1.527	1.502	1.501	1.525
8.0	1.481	1.389	1.325	1.285	1.266	1.269	1.295
8.1	1.179	1.107	1.057	1.027	1.016	1.022	1.049
8.2	0.9387	0.8828	0.8450	0.8232	0.8169	0.8263	0.8531
8.3	0.7481	0.7048	0.6762	0.6610	0.6589	0.6705	0.6976
8.4	0.5968	0.5634	0.5421	0.5321	0.5334	0.5468	0.5741
8.5	0.4766	0.4511	0.4357	0.4298	0.4337	0.4485	0.4760
8.6	0.3811	0.3619	0.3511	0.3485	0.3545	0.3704	0.3981
8.7	0.3052	0.2910	0.2839	0.2839	0.2916	0.3083	0.3362
8.8	0.2450	0.2347	0.2305	0.2326	0.2417	0.2591	0.2871
8.9	0.1971	0.1900	0.1881	0.1919	0.2020	0.2199	0.2480
9.0	0.1591	0.1545	0.1545	0.1595	0.1705	0.1889	0.2170

- (d) This subsection establishes surface water quality for cold-water fish. The Waters designated by the Indiana department of natural resources for put-and-take trout fishing and listed in section 5(a)(3) of this rule are designated as salmonid waters and shall must be protected for cold-water fish. In addition to subsections (b) and (c), the following criteria are established to ensure conditions necessary for the maintenance of a well-balanced, cold-water fish community and are applicable at any point in the waters outside of the applicable a mixing zone, as determined in accordance with section 7 of this rule, in the surface waters designated as salmonid waters to ensure conditions necessary for the maintenance of a well-balanced, cold-water fish community:
 - (1) Dissolved oxygen concentrations shall must not be less than:
 - (A) six (6.0) milligrams per liter at any time; and
 - (B) seven (7.0) milligrams per liter in areas where spawning occurs during the spawning season and in areas used for imprinting during the time salmonids are being imprinted.

Dissolved oxygen concentrations in the open waters of Lake Michigan shall must not be less than seven (7.0) milligrams per liter at any time.

- (2) The maximum temperature rise above natural shall must not exceed two (2) degrees Fahrenheit (one and one-tenth (1.1) degrees Celsius) at any time or place and, unless due to natural causes, the temperature shall must not exceed the following:
 - (A) Seventy (70) degrees Fahrenheit (twenty-one and one-tenth (21.1) degrees Celsius) at any time.
 - (B) Sixty-five (65) degrees Fahrenheit (eighteen and three-tenths (18.3) degrees Celsius) during spawning or imprinting periods.
- (e) This subsection establishes Bacteriological quality for recreational uses during the recreational season is as follows:
 - (1) The recreational season is defined as the months of April through October, inclusive.
 - (2) In addition to subsection (b), the criteria in this subsection shall are to be used to do the following:

- (A) Evaluate waters for full body contact recreational uses.
- (B) Establish wastewater treatment requirements.
- (C) Establish effluent limits during the recreational season.
- (3) For full body contact recreational uses, E. coli bacteria shall must not exceed the following:
 - (A) One hundred twenty-five (125) **colony forming units (cfu) or most probable number (MPN)** per one hundred (100) milliliters as a geometric mean based on not less than five (5) samples equally spaced over a thirty (30) day period.
 - (B) Two hundred thirty-five (235) **cfu or MPN** per one hundred (100) milliliters in any one (1) sample in a thirty (30) day period, except that, in cases where there are at least ten (10) samples at a given site, up to ten percent (10%) of the samples may exceed two hundred thirty-five (235) cfu or MPN per one hundred (100) milliliters where **the:**
 - (i) the E. coli exceedances are incidental and attributable solely to E. coli resulting from the discharge of treated wastewater from a wastewater treatment plant as defined at IC 13-11-2-258; and
 - (ii) the criterion in clause (A) is met.

However, a single sample shall be is used for making beach notification and closure decisions.

If a geometric mean cannot be calculated because five (5) equally spaced samples are not available, then the criterion stated in clause (B) must be met.

- (4) For demonstrating compliance with wastewater treatment requirements, sanitary wastewater dischargers shall ensure the following:
 - (A) The concentration of E. coli in the undiluted discharge does not exceed one hundred twenty-five (125) cfu or MPN per one hundred (100) milliliters as a geometric mean of the effluent samples taken in a calendar month.
 - (B) Not more than ten percent (10%) of all samples when not less than ten (10) samples are taken and analyzed for E. coli in a calendar month exceed two hundred thirty-five (235) cfu or MPN per one hundred (100) milliliters as a daily maximum. Under this clause, the calculation of ten percent (10%) of the samples taken shall must be limited to the lowest whole number result.
- (5) Effluent limits to implement the criteria in subdivision (3) during the recreational season shall **must** be established in NPDES permits by incorporating the following that are to be applied to the undiluted discharge:
 - (A) The concentration of E. coli in the undiluted discharge shall must not exceed one hundred twenty-five (125) cfu or MPN per one hundred (100) milliliters as a geometric mean of the effluent samples taken in a calendar month.
 - (B) Not more than ten percent (10%) of all samples in a calendar month exceed two hundred thirty-five (235) cfu or MPN per one hundred (100) milliliters as a daily maximum. Under this clause, the calculation of ten percent (10%) of the samples taken shall **must** be limited to the lowest whole number result.
- (f) This subsection establishes surface water quality for public water supply. In addition to subsection (b), the following criteria are established to protect the surface water quality at the point at which water is withdrawn for treatment for public water supply are as follows:
 - (1) The coliform bacteria group shall must not exceed the following:
 - (A) Five thousand (5,000) **cfu or MPN** per one hundred (100) milliliters as a monthly average value (either MPN or **membrane filter** (MF) count).
 - (B) Five thousand (5,000) **cfu or MPN** per one hundred (100) milliliters in more than twenty percent (20%) of the samples examined during any month.
 - (C) Twenty thousand (20,000) **cfu or MPN** per one hundred (100) milliliters in more than five percent (5%) of the samples examined during any month.
 - (2) Taste and odor producing substances, other than those naturally occurring, shall must not interfere with the production of a finished water by conventional treatment consisting of the following:
 - (A) Coagulation.
 - (B) Sedimentation.
 - (C) Filtration.
 - (D) Disinfection.
 - (3) The concentrations of either chloride or sulfate shall must not exceed two hundred fifty (250) milligrams per liter unless due to naturally occurring sources.
 - (4) The concentration of dissolved solids shall must not exceed seven hundred fifty (750) milligrams per liter unless due to naturally occurring sources. A specific conductance of one thousand two hundred (1,200) micromhos per centimeter (at twenty-five (25) degrees Celsius) may be considered equivalent to a dissolved solids concentration of seven hundred fifty (750) milligrams per liter.
 - (5) Surface waters shall be considered **are** acceptable for public water supply if radium-226 and strontium-90 are present in amounts not exceeding three (3) and ten (10) picocuries per liter, respectively. In the known absence of strontium-90 and alpha emitters, the water supply is acceptable when the gross beta

concentrations do not exceed one thousand (1,000) picocuries per liter.

- (6) The:
 - (A) combined concentration of nitrate-N and nitrite-N shall must not exceed ten (10) milligrams per liter; and
 - (B) concentration of nitrite-N shall must not exceed one (1) milligram per liter.
- (7) Chemical constituents in the waters shall must not be present in such at levels as to that prevent, after conventional treatment, meeting the drinking water standards contained in 327 IAC 8-2, due to other than natural causes.
- (g) This subsection establishes surface water quality for industrial water supply. In addition to subsection (b), the criterion to ensure protection of water quality at the point at which water is withdrawn for use (either with or without treatment) for industrial cooling and processing is that, other than from naturally occurring sources, the dissolved solids shall must not exceed seven hundred fifty (750) milligrams per liter at any time, other than from naturally occurring sources, to ensure protection of water quality at the point at which surface water is withdrawn for use, either with or without treatment, for industrial cooling and processing. A specific conductance of one thousand two hundred (1,200) micromhos per centimeter (at twenty-five (25) degrees Celsius) may be considered equivalent to a dissolved solids concentration of seven hundred fifty (750) milligrams per liter.
- (h) This subsection establishes surface water quality for agricultural uses. The criteria to ensure **surface** water quality conditions necessary for agricultural use are the same as those in subsection (b).
- (i) This subsection establishes surface water quality for limited uses. The quality of **surface** waters designated for limited uses under section 19(a) of this rule shall, **must**, at a minimum, meet the following criteria (1) The eriteria contained in subsection subsections (b), (2) The criteria contained in subsection (e), (3) The criteria contained in subsection and (g), (4) The waters must and be aerobic at all times. (5) Notwithstanding subdivisions (1) through (4), the quality of a limited use stream However, the water must meet the criteria that are applicable to the higher use water at the point where it a limited use water:
 - (1) becomes physically or chemically capable of supporting a higher use; or at its interface
 - (2) interfaces with a higher use water segment. shall meet the criteria that are applicable to the higher use water.
 - (j) Additional requirements for the open waters of Lake Michigan are as follows:
 - (1) In addition to complying with all other applicable subsections, open waters in Lake Michigan shall must meet the following criteria:

Table 8-9 Additional Criteria for Lake Michigan

Parameters	Criteria
Dissolved oxygen	Dissolved oxygen concentrations shall must not be less than seven (7.0) milligrams per liter at any time at all places outside the applicable mixing zone.
pН	No pH values below six (6.0) or above nine (9.0) are permitted , except daily fluctuations that exceed pH 9.0 and are correlated with photosynthetic activity. shall be permitted.
Chloride	250 mg/l ^[1]
Phenols	See The criteria in subsection (c)(1)
Sulfate	250 mg/l ^[1]
Total phosphorus	See The requirements in 327 IAC 5-10-2
Total dissolved solids	750 mg/l ^[1]
Fluoride	1.0 mg/l ^[1]
Dissolved iron	300 μg/l ^[1]

^[1] This criterion is established to minimize or prevent minimizes or prevents increased levels of this substance in Lake Michigan. For the purposes of establishing water quality-based effluent limitations (WQBEL) based on this criterion, it shall must be treated as a four (4) day average criterion.

(2) During each triennial review of the water quality standards, prior to preliminary adoption of revised rules, the **following must occur:**

- **(A) The** department shall prepare a report for the water pollution control board on the monitoring data for the constituents parameters in the following table Table 8-10, as measured at the drinking water intakes in Lake Michigan.
- **(B)** If these the monitoring data in clause (A) indicate that the levels of the constituents parameters are either increasing or exceed the levels in the Table 8-10, the report shall for the board must provide available information on the known and potential causes of the increased levels of these parameters, the known and potential impacts on aquatic life, wildlife, and human health, and any recommended revisions of the criteria.

Table 8-10

1 45.0 0 10	
Parameters	Levels
рН	7.5-8.5 s.u.
Chloride	
Monthly average	15 mg/l
Daily maximum	20 mg/l
Sulfate	
Monthly average	26 mg/l
Daily maximum	50 mg/l
Total phosphorus	
Monthly average	0.03 mg/l
Daily maximum	0.04 mg/l
Total dissolved solids	
Monthly average	172 mg/l
Daily maximum	200 mg/l

*This document is incorporated by reference. Copies may be obtained from the U.S. EPA National Service Center for Environmental Publications (www.epa.gov/nscep), or are available for review at the Indiana Department of Environmental Management, Office of Legal Counsel, Indiana Government Center North, Thirteenth Floor, 100 North Senate Avenue, Indianapolis, Indiana 46204.

(Water Pollution Control Division; <u>327 IAC 2-1.5-8</u>; filed Jan 14, 1997, 12:00 p.m.: 20 IR 1370; errata filed Aug 11, 1997, 4:15 p.m.: 20 IR 3376; filed Feb 14, 2005, 10:05 a.m.: 28 IR 2074; errata filed Apr 6, 2006, 2:48 p.m.: 29 IR 2546; filed Mar 18, 2008, 2:26 p.m.: <u>20080416-IR-327060573FRA</u>; filed Jul 9, 2012, 2:54 p.m.: <u>20120808-IR-327110320FRA</u>; filed Nov 5, 2021, 12:56 p.m.: <u>20211201-IR-327140058FRA</u>)

LSA Document #14-58(F)

Proposed Rule: 20210421-IR-327140058PRA

Hearing Held: August 11, 2021

Approved by Attorney General: October 26, 2021 Approved by Governor: November 2, 2021 Filed with Publisher: November 5, 2021, 12:56 p.m.

Documents Incorporated by Reference: Aquatic Life Ambient Water Quality Criterion for Selenium – Freshwater, EPA-822-R-16-006, Appendix K: Translation of a Selenium Fish Tissue Criterion Element to a Site-Specific Water Column Value (June 2016)

Small Business Regulatory Coordinator: Angela Taylor, IDEM Small Business Regulatory Coordinator/CTAP Small Business Liaison, IGCN 1316, 100 North Senate Avenue, Indianapolis, IN 46204-2251, (317) 233-0572 or (800) 988-7901, ctap@idem.in.gov

Small Business Assistance Program Ombudsman: Erin Moorhous, IDEM Small Business Assistance Program Ombudsman/Business, Agricultural, and Legislative Liaison, IGCN 1301, 100 North Senate Avenue, Indianapolis, IN 46204-2251, (317) 232-8921 or (800) 451-6027, emoorhous@idem.in.gov

Posted: 12/01/2021 by Legislative Services Agency

An html version of this document.